

hp LaserJet 3015

invent

use

hp LaserJet 3015 all-in-one

User Guide

Copyright Information

© Copyright 2003 Hewlett-Packard Development Company, L.P.

Reproduction, adaptation or translation without prior written permission is prohibited, except as allowed under the copyright laws.

The information contained herein is subject to change without notice.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

A user of the Hewlett-Packard product associated with this user guide is granted a license to: a) print hard copies of this user guide for PERSONAL, INTERNAL or COMPANY use subject to the restriction not to sell, re-sell or otherwise distribute the hard copies; and b) place an electronic copy of this user guide on a network server, provided access to the electronic copy is limited to PERSONAL, INTERNAL users of the Hewlett-Packard product associated with this user guide.

Part number: Q2669-90902

Edition 1, 10/2003

Trademark Credits

Adobe® and PostScript® are trademarks of Adobe Systems Incorporated.

Microsoft®, Windows®, and Windows NT® are U.S. registered trademarks of Microsoft Corporation.

UNIX® is a registered trademark of The Open Group.

All other products mentioned herein may be trademarks of their respective companies.

Hewlett-Packard Development Company, L.P.
20555 S.H. 249
Houston, TX 77070

Table of contents

1 Getting to know your device

Identifying the hp LaserJet 3015 all-in-one 2
    Package contents 2
Device features 3
Identifying the hardware components 4
    HP LaserJet 3015 all-in-one hardware components 4
Identifying the device control panel components 5
Identifying the software components 6
Print-media specifications 7
    Supported paper weights and sizes 7

2 Changing the settings by using the hp toolbox or the device control panel

Using the hp toolbox 10
    Supported operating systems 10
    Supported browsers 10
    To view the hp toolbox 10
    The hp toolbox sections 11
Using the device control panel 13
    Printing a configuration page 13
    Printing a device control panel menu map 13
    Restoring the factory-set defaults 13
    Changing the device control panel display language 14
    Changing the default media size 14
    Using the device volume controls 14

3 Printing

Printing by using manual feed 18
    To print by using manual feed 18
Stopping or canceling a print job 19
Printer drivers 20
    Changing print settings 20
Understanding print-quality settings 21
    To temporarily change print-quality settings 21
    To change print-quality settings for all future jobs 21
    To use EconoMode (to save toner) 21
Optimizing print quality for media types 23
    To gain access to the optimizing feature 23
Device media specifications 24
Guidelines for using media 25
    Paper 25
    Common media problems table 25
    Labels 25
    Transparencies 26

Envelopes 26
Card stock and heavy media 27
Selecting media for the automatic document feeder (ADF) 29
Automatic document feeder (ADF) specifications 29
Printing on envelopes 30
To print on one envelope 30
To print on multiple envelopes 31
Printing on transparencies and labels 33
To print on transparencies or labels 33
Printing on letterhead and preprinted forms 35
To print on letterhead and preprinted forms 35
Printing on custom-sized media or card stock 36
To print on custom-sized media or card stock 36
Printing on both sides of the media (manual duplexing) 37
To manually duplex 37
Printing multiple pages on a single sheet of media 39
To print multiple pages on a single sheet 39
Printing booklets 40
To print booklets 40
Printing watermarks 42
To use the watermark feature 42

4 Copying

Loading originals to copy 44
To load originals into the automatic document feeder (ADF) input tray 44
Starting a copy job 46
Canceling a copy job 46
Adjusting the copy quality 47
To adjust the copy quality for the current job 47
To adjust the default copy quality 47
Adjusting the lighter/darker (contrast) setting 48
To adjust the lighter/darker setting for the current job 48
To adjust the default lighter/darker setting 48
Reducing or enlarging copies 49
To reduce or enlarge copies for the current job 50
To change the default copy size 50
Changing the default copy-collation setting 52
To change the default copy-collation setting 52
Changing the default number of copies 53
To change the default number of copies 53
Copying two-sided originals 54
To copy a multiple-page stack of two-sided originals 54

5 Scanning

Loading originals to scan 56
Loading originals into the automatic document feeder (ADF) input tray 56
Understanding scanning methods 58
Canceling a scan job 59
Scanning from the device control panel 60
Programming the Scan to button 60
Scanning to e-mail 60
Scanning to a folder 60
Scanning by using hp LaserJet Scan software 61
Scanning to e-mail 61
To scan to a file 61

Scanning to another software program 62
Scanning to the Readiris OCR software 63
Scanning by using TWAIN-compliant and WIA-compliant software 64
Using TWAIN-compliant and WIA-compliant software 64
Scanning by using OCR 65
Readiris 65
Scanner resolution and color 66
Resolution and color guidelines 66
Color 67

6 Faxing

..... 70
..... 70

7 Cleaning and maintenance

Cleaning the outside of the device 72
To clean the exterior 72
To clean the glass 72
Cleaning the media path 73
To clean the media path 73

8 Troubleshooting

Device does not turn on 76
Is power reaching the device? 76
The device control panel display has black lines or dots, or fades 77
Black lines or dots 77
Faded device control panel display 77
Pages print but are totally blank 78
Is the sealing tape still in the print cartridge? 78
Does the configuration page print? 78
Does the document contain blank pages? 78
Is the original loaded correctly? 78
Pages did not print 79
Does a message appear on your computer screen? 79
Is media being pulled into the device correctly? 79
Are media jams present? 79
Is the parallel or USB Device Cable (A/B) working, and is it connected correctly? 79
Are other devices running on your computer? 79
Pages printed, but a problem exists 80
Is the print quality poor? 80
Is the printed page different from what appears onscreen? 80
Are the device settings appropriate for the print media? 80
Onscreen error messages appear 81
Printer not responding/error writing to LPT1 81
Cannot access port (in use by another application) 81
Paper-handling problems exist 82
Print is skewed (crooked) 82
More than one sheet feeds at one time 82
Device does not pull media from the media input tray 82
Media curls when fed through device 82
Printed page is different from what appears onscreen 83
Is the text garbled, incorrect, or incomplete? 83
Are graphics or text missing? Are there blank pages? 83
Is the page format different from the format on another printer? 84

Is the quality of the graphics poor? 84
Media jams occur in the printer 85
To clear a media jam 85
To clear other media jams 87
Tips to avoid media jams 88
Print quality is unacceptable 89
Light print or fade 89
Toner specks 89
Dropouts 90
Vertical lines 90
Gray background 91
Toner smear 91
Loose toner 92
Vertical repetitive defects 92
Misformed characters 93
Page skew 93
Curl or wave 94
Wrinkles or creases 94
Toner scatter outline 95
Device control panel error messages appear 96
Resolving common error messages 96
Critical error messages 96
Alert messages 97
Warning messages 97
No copy came out 99
Is media loaded in the input tray? 99
Is the original loaded correctly? 99
Is the ADF media lever set correctly? 99
Copies are blank, or images are missing or faded 100
Has the sealing tape been removed from the print cartridge? 100
Is the print cartridge low on toner? 100
Is the original of poor quality? 100
Does the original have a colored background? 100
Copy quality is unacceptable 101
Preventing problems 101
Media jams occur in the automatic document feeder (ADF) 102
Typical automatic document feeder (ADF) jam locations 102
Automatic document feeder (ADF) media lever 102
To clear a media jam from the automatic document feeder (ADF) 103
Copy defects are apparent 104
Vertical white or faded stripes 104
Blank pages 104
Wrong original was copied 105
Too light or dark 105
Unwanted lines 105
Black dots or streaks 105
Unclear text 105
Reduced size 105
Scanned image is of poor quality 106
Is the original a second-generation photo or picture? 106
Is the image quality better when the document is printed? 106
Is the image skewed (crooked)? 106
Does the scanned image show blotting, lines, vertical white stripes, or any other defect? 106
Do graphics look different from the original? 106
Part of the image did not scan 107

Was the original loaded correctly? 107
Does the original have a colored background? 107
Are text or images on the back of a two-sided original appearing in the scan? 107
Is the original longer than 381 mm (15 inches)? 107
Is the original too small? 107
Is the media size correct? 107
The scan takes too long 108
Is your resolution or color level set too high? 108
Is your software set to scan in color? 108
Did you send a print job or copy job before you tried to scan? 108
Is your computer set for bidirectional communication? 108
Error messages appear 109
Common scanning error messages 109
Scan quality is unacceptable 110
Preventing problems 110
Blank pages 110
Too light or dark 110
Unwanted lines 110
Black dots or streaks 110
Unclear text 110

Appendix A Specifications

HP LaserJet 3015 all-in-one 113
HP LaserJet 3015 all-in-one specifications 113
HP LaserJet 3015 all-in-one battery 115

Appendix B Regulatory Information

..... 117
FCC regulations 118
Telephone consumer protection act (United States) 119
IC CS-03 requirements 120
Regulatory information for the European Union countries/regions 120
Safety statements 121
Laser safety statement 121
Canada DOC regulations 121
Laser statement for Finland 122
Korean EMI statement 122
Australia 123
Declaration of Conformity 124
Environmental product stewardship program 125
Protecting the environment 125
Ozone production 125
Energy consumption 125
Toner consumption 125
Paper use 125
Plastics 125
HP LaserJet printing supplies 126
HP printing supplies returns and recycling program information 126
U.S. returns 126
Non-U.S. returns 126
Paper 126
Material restrictions 126
Nederlands 127
For more information 127
Material safety data sheets 128

Appendix C HP limited warranty statement

HP LaserJet 3015 all-in-one ONE-YEAR LIMITED WARRANTY 129

Appendix D HP parts and accessories

Ordering HP parts and accessories 132
HP parts and accessories chart 132
HP LaserJet print cartridges 134
HP policy on non-HP print cartridges 134
To install a print cartridge 134
Storing print cartridges 134
Print cartridge life expectancy 134
Recycling print cartridges 134
Saving toner 135

Appendix E Service and support

Obtaining hardware service 138
To obtain hardware service 138
To remove the media input tray 139
Extended warranty 140
Service information form 141

Glossary

Index

1 Getting to know your device

Use these topics to acquaint yourself with your new HP LaserJet 3015 all-in-one:

- Identifying the hp LaserJet 3015 all-in-one
- Device features
- Identifying the hardware components
- Identifying the device control panel components
- Identifying the software components
- Print-media specifications

Identifying the hp LaserJet 3015 all-in-one

Use the following illustration to make sure that the package contents are complete.

Package contents



1 Print cartridge
2 Power cord
3 Getting started guide and support flyer
4 Media input tray
5 CD-ROMs containing device software and electronic user guide
6 Automatic document feeder (ADF) input tray
7 Fax guide
8 Phone cord
9 ADF output support
10 Ouput bin support
11 Control panel cover
12 HP LaserJet 3015 all-in-one

Note

Use the phone cord and the power cord that came with the device. Using other phone cords or power cords can adversely affect the performance of the device.

Learn more about the device by using these sources of information:

- **The HP toolbox.** Use this software component to perform many of the tasks described in this user guide and to set print, fax, copy, and scan settings.
- **The start guide.** Use this guide to set up the device, connect it to your computer, and install the software.
- **The fax guide**. Use this guide to set up and use the fax functions of the device.

Device features

Speed	• Prints and copies up to 15 pages per minute (ppm)
Paper handling	• A 30-page automatic document feeder (ADF), a 150-sheet media input tray, and a 10-sheet priority input slot
Memory	• 32 megabytes (MB) of random-access memory (RAM) (9 MB for the system and 23 MB of RAM available to the user)
Connectivity	• A universal serial bus (USB) port (compatible with 2.0 specifications) and an IEEE 1284-B parallel port (Note: cables are not included)
Fax	• Full-functionality fax capabilities with a V.34 fax, including a phone book, fax polling, and delayed-fax features

Identifying the hardware components

Use the following illustrations to identify the device hardware components.

HP LaserJet 3015 all-in-one hardware components





1 Automatic document feeder (ADF) input tray
2 ADF media lever
3 Device control panel
4 ADF output bin
5 Print-cartridge-door release
6 Device output bin
7 Priority input slot
8 Media input tray
9 Parallel port
10 USB port
11 Fax interface ports
12 Power switch
13 Power receptacle

Identifying the device control panel components

Use the following illustration to learn about the device control panel components.



1. **Fax controls.** Use the fax controls to send and receive faxes and to change commonly used fax settings. See the fax guide for information about using the fax controls.
2. **Alphanumeric buttons.** Use the alphanumeric buttons to type data into the device control panel display and dial phone numbers for faxing. For information about using alphanumeric key characters, see the fax guide.
3. **Menu and cancel controls.** Use these controls to select menu options, determine the device status, and cancel the current job.
4. **Copy controls.** Use these controls to change commonly used default settings and to start copying. For instructions about copying, see Copying.
5. **Scan controls.** Use these controls to scan to e-mail or to a folder. For instructions about scanning, see Scanning.

Identifying the software components

Note

The software components that are installed depend on the operating system (OS) and the installation type. See the start guide for more information.

The following software items are included with the device:

- HP toolbox
- HP LaserJet Scan
- TWAIN or WIA scan driver
- HP LaserJet Fax
- Readiris OCR (not installed with other software; separate installation is required)
- Printer drivers (PCL 6, PCL 5e, PostScript Level 2 emulation)
- Installer/uninstaller

Note

The PCL 6 printer driver is intalled automatically when you use the **Typical** option during the installation of the software. To install the PostScript Level 2 emulation printer driver, select the **Custom** option during the installation of the software. To install the PCL 5e printer driver, use the printer wizard after the software has been installed.

Print-media specifications

For optimum results, use conventional 75 g/m^2 to 90 g/m^2 (20 to 24 lb) photocopy paper. Verify that the paper is of good quality and is free of cuts, nicks, tears, spots, loose particles, dust, wrinkles, curls, or bent edges.

Note

The printer supports a wide range of standard and custom sizes of print media. The capacity of trays and bins can vary depending on media weight and thickness and environmental conditions. Smoothness—100 to 250 (Sheffield).

Use only transparencies designed for use with HP LaserJet printers.

Supported paper weights and sizes

Media input tray paper sizes

Media input tray	Dimensions	Weight or thickness	Capacity
Minimum-size paper	76 by 127 mm (3 by 5 in)	60 to 163 g/m^2 (16 to 43 lb bond)	150 sheets (60 g/m^2; 16 lb bond)
Maximum-size paper	216 by 356 mm (8.5 by 14 in)	60 to 163 g/m^2 (16 to 43 lb bond)	150 sheets (60 g/m^2; 16 lb bond)
Minimum-size glossy paper	76 by 127 mm (3 by 5 in)	75 to 120 g/m^2 (20 to 32 lb bond)	Maximum stack height: 18 mm (0.7 in)
Maximum-size glossy paper	216 by 356 mm (8.5 by 14 in)	75 to 120 g/m^2 (20 to 32 lb bond)	Maximum stack height: 18 mm (0.7 in)
Minimum-size transparencies	76 by 127 mm (3 by 5 in)	0.10 to 0.13 mm thick (4 to 5 mils thick)	75 sheets
Maximum-size transparencies	216 by 356 mm (8.5 by 14 in)	0.10 to 0.13 mm thick (4 to 5 mils thick)	75 sheets
Minimum-size envelopes	90 by 160 mm (3.5 by 6.3 in)	75 to 105 g/m^2 (20 to 28 lb bond)	15 envelopes
Maximum-size envelopes	178 by 254 mm (7 by 10 in)	75 to 105 g/m^2 (20 to 28 lb bond)	15 envelopes
Minimum-size label	76 by 127 mm (3 by 5 in)	60 to 216 g/m^2 (22 to 80 lb cover)	60 sheets
Maximum-size label	216 by 356 mm (8.5 by 14 in)	60 to 216 g/m^2 (22 to 80 lb cover)	60 sheets
Minimum-size card stock	76 by 127 mm (3 by 5 in)	135 to 157 g/m^2 (36 to 42 lb bond)	60 sheets
Maximum-size card stock	216 by 356 mm (8.5 by 14 in)	135 to 157 g/m^2 (36 to 42 lb bond)	60 sheets

Priority input slot paper sizes

Priority input slot	Dimensions	Weight or thickness	Capacity
Minimum-size paper	76 by 127 mm (3 by 5 in)	60 to 163 g/m^2 (16 to 43 lb bond)	10 sheets (75 g/m^2; 20 lb bond)
Maximum-size paper	216 by 356 mm (8.5 by 14 in)	60 to 163 g/m^2 (16 to 43 lb bond)	10 sheets (75 g/m^2; 20 lb bond)
Minimum-size glossy paper	76 by 127 mm (3 by 5 in)	75 to 120 g/m^2 (20 to 32 lb bond)	Maximum stack height: 1.5 mm (0.06 in)
Maximum-size glossy paper	216 by 356 mm (8.5 by 14 in)	75 to 120 g/m^2 (20 to 32 lb bond)	Maximum stack height: 1.5 mm (0.06 in)
Minimum-size transparencies	76 by 127 mm (3 by 5 in)	0.10 to 0.13 mm thick (4 to 5 mils thick)	5 sheets
Maximum-size transparencies	216 by 356 mm (8.5 by 14 in)	0.10 to 0.13 mm thick (4 to 5 mils thick)	5 sheets
Minimum-size envelopes	76 by 127 mm (3 by 5 in)	60 to 90 g/m^2 (16 to 24 lb bond)	Individual envelopes
Maximum-size envelopes	216 by 356 mm (8.5 by 14 in)	60 to 90 g/m^2 (16 to 24 lb bond)	Individual envelopes
Minimum-size label	76 by 127 mm (3 by 5 in)	60 to 216 g/m^2 (22 to 80 lb cover)	4 sheets
Maximum-size label	216 by 356 mm (8.5 by 14 in)	60 to 216 g/m^2 (22 to 80 lb cover)	4 sheets
Minimum-size card stock	76 by 127 mm (3 by 5 in)	135 to 163 g/m^2 (36 to 43 lb bond)	4 sheets
Maximum-size card stock	216 by 356 mm (8.5 by 14 in)	135 to 163 g/m^2 (36 to 43 lb bond)	4 sheets

Automatic document feeder (ADF) paper sizes

ADF	Dimensions	Weight or thickness	Capacity
Minimum-size paper	74 by 105 mm (2.9 by 4.1 in)	60 to 90 g/m^2 (16 to 24 lb bond)	30 sheets (75 g/m^2; 20 lb bond)
Maximum-size paper	215 by 356 mm (8.5 by 14 in)	60 to 90 g/m^2 (16 to 24 lb bond)	30 sheets (75 g/m^2; 20 lb bond)

Note

The ADF output bin holds one sheet of legal-size media (215 by 356 mm (8.5 by 14 inches)). Subsequent sheets of legal-size media slide off of the ADF output bin.

2 Changing the settings by using the hp toolbox or the device control panel

You can change the settings for the device by using the HP toolbox or the device control panel. Often, the easier method for changing the device settings is to use the HP toolbox.

The following table lists some of the settings that you can change by using the HP toolbox and the device control panel. For information about how to use the HP toolbox to change settings, see the HP toolbox Help. You can open the HP toolbox Help by clicking **How Do I** on the left side of the HP toolbox window. (See Using the hp toolbox for information about how to gain access to the HP toolbox.) For information about how to use the device control panel to change the device settings, review the information in this chapter.

Note Settings that are established in the software program take precedence over printer-driver settings. Printer-driver settings override the HP toolbox and device control panel settings.

Setting or feature	HP toolbox	Control panel
Restore the factory-set defaults.	X	X
Print information pages, such as the configuration page, device control panel menu map, and usage page.	X	X
Change the device control panel display language.	X	X
Change the HP toolbox language.	X	
Set up status alerts.	X	
Configure the fax-send and fax-receive settings.	X	X
View or forward faxes that have been received to the computer.	X	
Configure the scan to e-mail or a folder settings.	X	
Change the copy settings.	X	X
Add, delete, or modify the destinations in the Fax Phone Book.	X	X
Gain access to the online user guide.	X	
Check the device status remotely.	X	

Using the hp toolbox

The HP toolbox is a Web application that you can use for the following tasks.

- Monitor the device status.
- View and configure the device settings for print, fax, copy, and scan.
- View troubleshooting and "How do I" information.
- Provide access to fax and scan software capabilities.

You can view the HP toolbox when the device is directly connected to a computer, or when the device is connected to a network. You must have performed a complete software installation to use the HP toolbox.

Note You do not need Internet access to open and use the HP toolbox. However, if you click a link in the **Other Links** area, you must have Internet access to go to the site associated with the link. For more information, see Other links.

Supported operating systems

The HP toolbox is supported for the following operating systems:

- Windows 98, Windows 2000, Windows Millennium Edition (Me), and Windows XP

Note The transmission control protocol/Internet protocol (TCP/IP) must be installed in the operating system for the HP toolbox to function.

Supported browsers

To use the HP toolbox, you must have one of the following browsers:

- Microsoft Internet Explorer 5.5 or later
- Netscape Navigator 6.2 or later
- Opera 7.0 or later

All pages can be printed from the browser.

To view the hp toolbox

Open the HP toolbox in one of the following ways:

- On the desktop, double-click the HP toolbox icon.
- Double-click the Status Client icon that is located in the system tray, which is at the far right of the taskbar.
- On the **Start** menu, point to **HP LaserJet**, and then select **hp Toolbox**.

The HP toolbox opens in a Web browser.

Note After you open the URL, you can bookmark it so that you can return to it quickly in the future.

The hp toolbox sections

The HP toolbox contains the following sections:

- **Status** tab
- **Fax** tab
- **Scan to...** tab
- **Troubleshooting** tab
- **Documentation** tab

Other links

Each page in the HP toolbox contains links to the HP website for device registration and device support, and links for ordering supplies. You must have Internet access to use any of these links. If you use a dial-up connection and did not connect when you first opened the HP toolbox, you must connect before you can view these websites.

Status tab

The **Status** tab has links to the following main pages:

- **Device Status.** View device status information. This page indicates device conditions such as a media jam or an empty input tray. After you correct a problem with the device, click **Refresh** to update the device status.
- **Set up Status Alerts.** Use alerts to configure the device to notify you automatically of device alerts. From this page you can turn alerts on or off, specify when the device sends an alert, and select the type of alert (either a pop-up message or a taskbar icon) that you want to receive. To activate status alert settings, click **Apply**.
- **View Configuration.** View settings available for the device. This page also displays any accessories that have been installed, such as DIMMs. The **View Configuration** page displays the same information that is shown on the configuration page.
- **Print Info pages.** Print the configuration page and other information pages that are available for the device.

Fax tab

The **Fax** tab has links to the following main pages:

- **Fax Tasks**
- **Fax Phone Book**
- **Fax Send Log**
- **Fax Data Properties**
- **Fax Reports**
- **Detailed Fax Settings**

Note For more information about fax functions and features, see the fax guide.

Scan to... tab

The **Scan to...** tab has links to the following main pages:

- **Scan to E-mail or a Folder**
- **Scan Preferences**

Note The scan preferences apply to only **Scan to E-mail or a Folder**.

Troubleshooting tab

The **Troubleshooting** tab has links to various device troubleshooting information, such as how to clear a media jam; how to resolve print-quality problems; and how to resolve fax, copy, or scan problems.

Documentation tab

The **Documentation** tab contains links to the following information sources:

- **User Guide.** The user guide contains information about using the device, warranty, specifications, and support. The user guide is available in both HTML and PDF format.
- **Late Breaking News.** This document contains late-breaking information about the device. It is available in English only.

Using the device control panel

You can also configure settings at the device control panel. This section describes how to perform the following tasks:

- Printing a configuration page
- Printing a device control panel menu map
- Restoring the factory-set defaults
- Changing the device control panel display language
- Changing the default media size
- Using the device volume controls
- Changing print settings

Printing a configuration page

You can see which device settings are currently selected by printing a configuration page.

To print a configuration page

1. Press MENU/ENTER.
2. Use the < or the > button to select **Reports**, and then press MENU/ENTER.
3. Use the < or the > button to select **Config report**, and then press MENU/ENTER.

The device exits the menu settings and prints the report.

Printing a device control panel menu map

You can see all of your device control panel menu options by printing a device control panel menu map.

To print a device control panel menu map

1. On the device control panel, press MENU/ENTER.
2. Use the < or the > button to select **Reports**, and then press MENU/ENTER.
3. Use the < or the > button to select **Menu structure**, and then press MENU/ENTER.

A menu map prints, showing all of the device control panel menu options.

Restoring the factory-set defaults

Restoring the factory-set defaults returns all of the settings to the factory defaults and clears the fax header name and phone number. (See the fax guide for information about how to add your information to the fax header.) This procedure clears fax numbers and names that are associated with one-touch keys and speed-dial codes, and deletes any pages that are stored in the memory. The procedure then automatically restarts the device.

To restore the factory-set defaults

1. Press MENU/ENTER.
2. Use the < or the > button to select **Service**, and then press MENU/ENTER.
3. Use the < or the > button to select **Restore defaults**, press MENU/ENTER, and then press MENU/ENTER again to confirm your selection.

The device automatically restarts.

Changing the device control panel display language

Use this procedure to have reports print in, and messages on the the device control panel display appear in, a language other than the default for your country/region.

Note The Demo page prints in English only.

To change the device control panel display language

1. Press MENU/ENTER.
2. Use the < or the > button to select **Common settings**, and then press MENU/ENTER.
3. Use the < or the > button to select **Language**, and then press MENU/ENTER.
4. Use the < or the > button to select the language that you want.
5. Press MENU/ENTER to save your selection.

The device automatically restarts.

Changing the default media size

The media size should be set to the size of media that you normally load in the media input tray. The device uses this setting for copying, printing reports, printing faxes, and determining autoreduction for incoming faxes.

To change the default paper size

1. Press MENU/ENTER.
2. Use the < or the > button to select **Common settings**, and then press MENU/ENTER.
3. Use the < or the > button to select **Def. paper size**, and then press MENU/ENTER.
4. Use the < or the > button until the size of paper that you have loaded appears. You can select **Letter**, **Legal**, or **A4**.
5. Press MENU/ENTER to save your selection.

Using the device volume controls

You can control the volume of the following sounds:

- The alarm sound that the device emits when it requires attention, such as when the device door is open.
- The beeps that are emitted when you press the device control panel buttons.

- The phone line sounds for outgoing faxes.
- The ring volume for incoming faxes.

To change the alarm volume

The alarm sounds when the device is presenting an alert or critical error message. The alarm duration length is either one or three seconds, depending on the type of error.

1. Press MENU/ENTER.
2. Use the < or the > button to select **Common settings**, and then press MENU/ENTER.
3. Use the < or the > button to select **Volume settings**, and then press MENU/ENTER.
4. Press MENU/ENTER to select **Alarm volume**.
5. Use the < or the > button to select **Off**, **Soft**, **Medium**, or **Loud**.
6. Press MENU/ENTER to save your selection.

Note The factory-set default for the alarm volume is **Soft**.

To change the volume for the fax

This setting determines the volume of various fax sounds that occur when the device is sending or receiving fax jobs.

1. Press MENU/ENTER.
2. Use the < or the > button to select **Common settings**, and then press MENU/ENTER.
3. Use the < or the > button to select **Volume settings**, and then press MENU/ENTER.
4. Use the < or the > button to select **PhoneLine Volume**, and then press MENU/ENTER.
5. Use the < or the > button to select **Off**, **Soft**, **Medium**, or **Loud**.
6. Press MENU/ENTER to save your selection.

Note The factory-set default is **Soft**.

To change the ring volume of the fax

The fax ring sounds when the device is initially sending or receiving a call. The ring duration length depends on the local telecom ring-pattern length.

1. Press MENU/ENTER.
2. Use the < or the > button to select **Common settings**, and then press MENU/ENTER.
3. Use the < or the > button to select **Volume settings**, and then press MENU/ENTER.
4. Press the < or the > button once to select **Ring volume**, and then press MENU/ENTER.
5. Use the < or the > button to select **Off**, **Soft**, **Medium**, or **Loud**.
6. Press MENU/ENTER to save your selection.

Note The factory-set default is **Soft**.

To change the device control panel key-press volume

The key-press volume controls the sound that is made when a device control panel button is pressed.

1. Press MENU/ENTER.
2. Use the < or the > button to select **Common settings**, and then press MENU/ENTER.
3. Use the < or the > button to select **Volume settings**, and then press MENU/ENTER.
4. Use the < or the > button to select **Key Press volume**, and then press MENU/ENTER.
5. Use the < or the > button to select **Off**, **Soft**, **Medium**, or **Loud**.
6. Press MENU/ENTER to save your selection.

Note The factory-set default for the device control panel key-press volume is **Soft**.

3 Printing

Use the following information to perform printing tasks with the device:

- Printing by using manual feed
- Stopping or canceling a print job
- Printer drivers
- Understanding print-quality settings
- Optimizing print quality for media types
- Device media specifications
- Guidelines for using media
- Selecting media for the automatic document feeder (ADF)
- Printing on envelopes
- Printing on transparencies and labels
- Printing on letterhead and preprinted forms
- Printing on custom-sized media or card stock
- Printing on both sides of the media (manual duplexing)
- Printing multiple pages on a single sheet of media
- Printing booklets
- Printing watermarks

Printing by using manual feed

Use manual feed when printing on mixed media (for example, printing on an envelope, then a letter, then an envelope, and so on). Load an envelope in the priority input tray and load letterhead in the media input tray.

To print by using manual feed

1. Open the device properties or printer setup (printer driver) in the software program.
2. On the **Paper** tab or the **Paper/Quality** tab, select **Manual Feed (Tray 1)** from the **Source is:** or **Paper Source** drop-down list. (For instructions about opening the printer driver from your computer, see Understanding print-quality settings.)
3. Send the print job.
4. After you have changed the setting, wait until **Manual feed** appears on the device control panel, and then press MENU/ENTER to print each job.

Stopping or canceling a print job

If your print job is currently printing, you can cancel it by pressing CANCEL on the device control panel.

CAUTION

Pressing CANCEL clears the job that the device is currently processing. If more than one process is running (for example, the device is printing a document while receiving a fax), pressing CANCEL clears the process that currently appears on the device control panel.

You can also cancel a print job from a software program or a print queue.

To stop the print job immediately, remove the remaining print media from the device. After printing stops, use one of the following options:

- **Device control panel:** To cancel the print job, press and release CANCEL on the device control panel.
- **Software program:** Typically, a dialog box appears briefly on the computer screen, allowing you to cancel the print job.
- **Windows print queue:** If a print job is waiting in a print queue (computer memory) or print spooler, delete the job there. Go to the **Printer** screen in Windows 98, Windows Me, Windows 2000, and Windows XP. Click **Start**, **Settings**, and **Printers**. Double-click the device icon to open the window, select your print job, and then click **Delete**.

Printer drivers

When you installed the device software, you selected one of the following printer drivers:

PCL 6 driver (default driver): Use the PCL 6 driver to take full advantage of the device features. Unless complete backward compatibility with previous printer control language (PCL) drivers or older printers is necessary, the PCL 6 driver is recommended.

PCL 5e driver: Use the PCL 5e driver if you need print results to look consistent with those from older HP LaserJet printers. Certain features (FastRes 1200 and 300 dpi) are not available in this driver. (Do not use the PCL 5e driver that is provided with this device with older printers.)

PS driver: Use the PostScript® (PS) driver for compatibility with PS needs. Certain features (manual duplexing, printing booklets, watermarks, and printing more than four pages per sheet) are not available with this driver.

Note The device automatically switches between PS emulation and PCL printer languages depending on the driver that you have selected. The PS emulation emulates Adobe® PostScript Level 2. For information about gaining access to your printer driver see Changing print settings.

Changing print settings

After installation, you can gain access to print settings from the device printer driver or from another software program. These settings do not affect other users on a network.

You can also change some of the printer settings through the HP toolbox. For more information about the HP toolbox, see Using the hp toolbox.

To change default settings across all programs

Windows 98, Windows Me, and Windows XP Home: From the **Start** menu, point to **Settings**, and then click **Printers**. Right-click the device icon, and then click **Properties**. Make the necessary changes to the settings, and then click **OK**.

Windows NT 4.0, Windows 2000, and Windows XP Professional: From the **Start** menu, point to **Settings**, and then click **Printers**. For Windows 2000, right-click the device icon, and then click **Printing Preferences**. For Windows NT 4.0, right-click the device icon, and then click **Document Defaults**.Make the necessary changes to the settings, and then click **OK**.

Note The actual steps can vary; these are the most common methods.

To change settings for a print job

On the **File** menu, click **Print**. In the **Print** dialog box, click **Properties**. Change the settings that you want to apply for the current print job, and then click **OK**.

Understanding print-quality settings

Print-quality settings affect how light or dark the print is on the page and the style in which the graphics are printed. You can also use the print-quality settings to optimize the print quality for a specific media type. See Optimizing print quality for media types for more information.

You can change the settings in the device properties to accommodate the types of jobs that you are printing. The following settings are available, depending on the printer driver that you are using:

- **Best Quality (FastRes 1200):** The resolution is rendered differently so that the job can print faster. This is the default setting.
- **600 dpi**
- **300 dpi**
- **Custom:** This setting produces the same resolution as the Faster Printing setting, but you can change the scale patterns.
- **EconoMode (Save Toner):** Text is printed with less toner. This setting is useful when you are printing drafts. You can use this setting independently of other print-quality settings.

Note Changing the resolution can change the formatting of your text.

To temporarily change print-quality settings

To change the print-quality settings only for the current software program, open the properties through the **Print Setup** menu in the program that you are using to print. See Changing print settings for more information.

To change print-quality settings for all future jobs

For Windows 98, Windows 2000, and Windows Me:

1. In the Windows system tray, click **Start**, select **Settings**, and then click **Printers**.
2. Right-click the device icon.
3. Click **Properties** (in Windows 2000, you can also click **Printing Preferences**).
4. Change the settings, and click **OK**.

For Windows XP:

1. In the Windows system tray, click **Start**, select **Settings**, and then click **Printers and Faxes**.
2. Right-click the device icon.
3. Click **Properties**, or click **Printing Preferences**.
4. Change the settings, and click **OK**.

To use EconoMode (to save toner)

EconoMode is a feature that allows the device to use less toner per page. Selecting this option extends the life of the toner supply and reduces the cost per page. However, it also reduces print quality. The printed image is lighter, but it is adequate for printing drafts or proofs.

Hewlett-Packard does not recommend full-time use of EconoMode. If EconoMode is used full-time when the average toner coverage is significantly less than five percent, it is possible that the toner supply will outlast the mechanical parts in the print cartridge. If print quality begins to degrade under these circumstances, you will need to install a new print cartridge, even if toner remains in the cartridge.

Note Not all device features are available from all printer drivers or operating systems. See the device properties (driver) online Help for information about available features for the driver.

1. To enable EconoMode, open the device properties (or printing preferences in Windows 2000 and Windows XP). See Changing print settings for more information.
2. On the **Paper/Quality** tab or the **Finishing** tab, select the **EconoMode** check box.

Note See To change print-quality settings for all future jobs for instructions about using the EconoMode setting for all future print jobs.

Optimizing print quality for media types

Media type settings control the temperature of the device fuser. You can change the settings for the print media that you are using to optimize the print quality. The following are the media types that you can optimize for:

- plain paper
- preprinted paper
- prepunched paper
- letterhead
- transparency
- labels
- bond paper
- recycled paper
- color paper
- light paper (less than 75 g/m^2 or 20 lb)
- heavy paper (90 to 105 g/m^2 or 24 to 28 lb)
- card stock (105 to 176 g/m^2 or 28 to 47 lb)
- envelope
- rough paper

To gain access to the optimizing feature

You can gain access to the optimizing feature on the **Paper** tab or the **Paper/Quality** tab in the device properties (printer driver). For more information, see Changing print settings.

Note

Printing speeds might vary depending on the type and size of media used.

You might need to change the setting again to optimize for the type of media on which you normally print.

Device media specifications

HP LaserJet devices produce excellent print quality. The device prints on a variety of media, such as cut-sheet paper (including recycled paper), envelopes, labels, transparencies, and custom-sized media. Properties such as weight, grain, and moisture content are important factors affecting device performance and output quality.

The device can use a variety of paper and other print media in accordance with the guidelines in this user guide. Media that does not meet these guidelines might cause the following problems:

- poor print quality
- increased media jams
- premature wear on the device, requiring repair

For best results, use only HP-brand paper and print media. Hewlett-Packard Company cannot recommend the use of other brands. Because they are not HP products, HP cannot influence or control their quality.

It is possible for media to meet all of the guidelines in this user guide and still not produce satisfactory results. This might be the result of improper handling, unacceptable temperature and humidity levels, or other variables over which Hewlett-Packard has no control.

Before you purchase a large quantity of media, make sure that it meets the requirements specified in this user guide and in the *HP LaserJet Printer Family Print Media Guide*. (See Ordering HP parts and accessories for more information about ordering the guidelines.) Always test media before you purchase a large quantity.

CAUTION Using media that does not meet Hewlett-Packard specifications might cause problems for the device, requiring repair. This repair is not covered by the Hewlett-Packard warranty or service agreements.

Note For information about supported media sizes, weights, and other specifications, see Print-media specifications.

Guidelines for using media

Use the guidelines in this section when selecting and using print media.

Paper

For best results, use conventional paper. Make sure that the paper is of good quality and free of cuts, nicks, tears, spots, loose particles, dust, wrinkles, voids, and curled or bent edges.

If you are unsure about what type of paper you are loading (such as bond or recycled), check the label on the package.

Some paper causes print quality problems, jamming, or damage to the device.

Note

Do not use letterhead that is printed with low-temperature inks, such as those used in some types of thermography.

Do not use raised letterhead.

The device uses heat and pressure to fuse toner to the media. Make sure that any colored media or preprinted forms use inks that are compatible with the device temperature (200° C or 392° F for 0.1 second).

Common media problems table

Symptom	Problem with media	Solution
Poor print quality or toner adhesion, or problems with feeding.	Too moist, too rough, too smooth, or embossed. Faulty media lot.	Try another kind of media between 100 and 250 Sheffield and 4 to 6 percent moisture content.
Dropouts, jamming, or curl.	Media has been stored improperly.	Store media flat in its moisture-proof wrapping.
Increased gray background shading.	The media weight is too heavy.	Use lighter media.
Excessive curl, or problems with feeding.	Too moist, wrong grain direction, or short-grain construction.	Use long-grain media.
Jamming, or damage to device.	Cutouts or perforations.	Do not use media with cutouts or perforations.
Problems with feeding.	Ragged edges.	Use good-quality media.

Labels

Note

For best results, use only HP-brand labels. To order HP supplies, visit http://www.hp.com.

When selecting labels, consider the quality of the following factors:

- **Adhesives:** The adhesive material should be stable at 200° C (392° F), the device maximum temperature.
- **Arrangement:** Use only labels that have no exposed backing between them. Labels can peel off sheets that have spaces between the labels, causing serious jams.
- **Curl:** Before printing, labels must lie flat with no more than 13 mm (0.5 inch) of curl in any direction.
- **Condition:** Do not use labels that have wrinkles, bubbles, or other indications of separation. Never use a sheet of labels that has already been run through the device.

Transparencies

Transparencies must be able to withstand 200° C (392° F), the device maximum temperature.

Envelopes

When selecting envelopes, consider the quality of the following factors.

Envelope construction

Envelope construction is critical. Envelope fold lines can vary considerably, not only between manufacturers, but also within a box from the same manufacturer. Successful printing on envelopes depends on the quality of the envelopes, which includes the following factors:

- **Weight:** The weight of the envelope paper should not exceed 105 g/m^2 (28 lb), or jamming might result.
- **Construction:** Before printing, envelopes should lie flat with less than 6 mm (0.25 inch) curl and should not contain air. Envelopes that trap air might cause problems.
- **Condition:** Make sure that the envelopes are not wrinkled, nicked, or otherwise damaged.
- **Sizes:** Supported envelope sizes range from 90 by 160 mm (3.5 by 6.3 inches) to 178 by 254 mm (7 by 10 inches).

Envelopes with double-side seams

An envelope with double-side-seam construction has vertical seams at both ends of the envelope rather than diagonal seams. This style is more likely to wrinkle during printing. Make sure that the seam extends all the way to the corner of the envelope as shown in the following illustration:



Envelopes with adhesive strips or flaps

Envelopes with a peel-off adhesive strip or with more than one flap that folds over to seal must use adhesives that are compatible with the heat and pressure in the device (200° C or 392° F). The extra flaps and strips might cause wrinkling, creasing, or jams.

Envelope storage

Proper storage of envelopes contributes to good print quality. You should store envelopes flat. If air is trapped in an envelope, creating an air bubble, the envelope might wrinkle during printing.

Card stock and heavy media

You can print on many types of card stock from the input trays, including index cards and postcards. Some card stock performs better than others because the construction is better suited for feeding through a laser device.

For optimum device performance, do not use media heavier than 157 g/m^2 (42 lb). Media that is too heavy might cause misfeeds, stacking problems, media jams, poor toner fusing, poor print quality, or excessive mechanical wear.

Note You might be able to print on heavier media if you do not fill the input trays to capacity and if you use media with a smoothness rating of 100 to 180 Sheffield.

Card stock construction

- **Smoothness:** 135 to 157 g/m^2 (36 to 42 lb) card stock should have a smoothness rating of 100 to 180 Sheffield. 60 to 135 g/m^2 (16 to 36 lb) card stock should have a smoothness rating of 100 to 250 Sheffield.
- **Construction**: Card stock should lie flat with less than 5 mm (0.2 inch) of curl.

- **Condition:** Make sure that the card stock is not wrinkled, nicked, or otherwise damaged.
- **Sizes:** Use card stock that is within the following size ranges only:
  - **Minimum:** 76 by 127 mm ((3 by 5 inches))
  - **Maximum:** 216 by 356 mm ((8.5 by 14 inches))

Note The ADF output bin holds one sheet of legal-size media (215 by 356 mm (8.5 by 14 inches)). Subsequent sheets of legal-size media slide off of the ADF output bin.

Card stock guidelines

Set margins at least 2 mm ((0.08) inch) away from the edges.

Selecting media for the automatic document feeder (ADF)

Use the following guidelines when selecting media for the ADF.

Automatic document feeder (ADF) specifications

- **Input capacity:** The ADF holds up to 30 sheets of flat, 60 to 90 g/m^2 (16 to 24 lb), copier-grade paper.
- **Media size**: Use copier-grade paper that is within the following size ranges only:
  - **Minimum**: 74 by 105 mm (2.9 by 4.1 inches)
  - **Maximum**: 215.9 by 356 mm (8.5 by 14 inches)

Note

The ADF is recommended only for paper faxing, copying, and scanning.

The ADF output bin holds one sheet of legal-size media (215 by 356 mm (8.5 by 14 inches)). Subsequent sheets of legal-size media slide off of the ADF output bin.

Printing on envelopes

Use one of the following methods to print on envelopes.

- To print on one envelope
- To print on multiple envelopes

To print on one envelope

Use only envelopes that are recommended for laser printers. See Device media specifications for more information.

Note Use the priority input slot for printing on one envelope. Use the media input tray for printing on multiple envelopes.

1. Before loading the envelope, slide the media guides outward so that they are slightly wider than the envelope.



2. If the envelope has a flap that folds along the long edge, place the flap-fold edge to the left, with the side to be printed on facing up. If the envelope has a flap that folds along the short edge, feed that edge into the device first, with the side to be printed on facing up.



3. Adjust the media guides to the width of the envelope.



4. On the **Paper** tab or the **Paper/Quality** tab in the printer driver, select **Envelope** from the **Type is:** drop-down list.

Note Not all device features are available for all printer drivers or operating systems. See the device properties (driver) online Help for information about the available features for the driver.

5. Print on the envelope.

To print on multiple envelopes

Use only envelopes that are recommended for laser printers. See Device media specifications for more information.

Note Use the priority input slot for printing on one envelope. Use the media input tray for printing on multiple envelopes.

1. Open the media input tray and remove any media.



2. Before loading the envelopes, slide the media guides outward so that they are slightly wider than the envelopes.



3. If the envelopes have a flap that folds along the long edge, place the flap-fold edge to the left, with the side to be printed on facing up. If the envelopes have a flap that folds along the short edge, feed that edge into the device first, with the side to be printed on facing up. Stack up to 15 envelopes.



4. Adjust the media guides to the length and width of the envelopes.



5. On the **Paper** tab or the **Paper/Quality** tab in the printer driver, select **Envelope** from the **Type is:** drop-down list.

Note

Not all device features are available for all printer drivers or operating systems. See the device properties (driver) online Help for information about the available features for the driver.

6. Print on the envelopes.

Printing on transparencies and labels

Use only transparencies and labels that are recommended for use in laser printers, such as HP transparency film and HP laser-quality labels. See Device media specifications for more information.

CAUTION Inspect the media to make sure that it is not wrinkled or curled and that it does not have any torn edges or missing labels. Do not send the labels through the device more than once. The adhesive can damage the device.

To print on transparencies or labels

CAUTION Be sure to set the correct media type in the device settings (printer driver) as instructed in the following procedure. The device adjusts the fuser temperature according to the media type setting. When printing on special media such as transparencies or labels, this adjustment prevents the fuser from damaging the media as it passes through the device.

1. Load a single page in the priority input slot or load multiple pages in the media input tray. Make sure that the top of the media is forward and the side to be printed on (the rough side of transparencies) is facing up.



2. Adjust the media guides.



3. On the **Paper** tab or the **Paper/Quality** tab in the printer driver, select the correct media type from the **Type is:** drop-down list.

Note

Not all device features are available for all printer drivers or operating systems. See the device properties (driver) online Help for information about the available features for the driver.

4. Print the document. Remove the media from the output bin as it exits to prevent it from sticking together, and place the printed pages on a flat surface.



Printing on letterhead and preprinted forms

Only use letterhead or preprinted forms that are recommended for use in laser printers, such as HP laser-quality letterhead and preprinted forms. See Device media specifications for more information.

Use these instructions to print documents on letterhead or preprinted forms.

To print on letterhead and preprinted forms

1. Load the print media with the top forward and the side to be printed on facing up.
2. Adjust the media guides to fit the width of the print media.
3. Print the document.

Note

To print a single-page cover letter on letterhead, followed by a multiple-page document, load the standard paper in the media input tray first, and then load the letterhead into the priority input slot. The device automatically prints from the priority input slot first.



Printing on custom-sized media or card stock

The device can print on custom-sized media and card stock that is between 76 by 127 mm (3 by 5 inches) and 216 by 356 mm (8.5 by 14 inches) in size. Depending on the media, you can print up to 10 sheets from the priority input slot. Use the media input tray for more than 10 sheets.

Note Make sure that the sheets are not stuck together before you load them.

To print on custom-sized media or card stock

1. Load the media with the narrow side forward and the side to be printed on facing up. Adjust the side and rear media guides to fit the media.



2. On the **Paper** tab or the **Paper/Quality** tab in the printer driver, click **Custom**. Specify the dimensions of the custom-sized media.

Note Not all device features are available for all printer drivers or operating systems. See the device properties (driver) online Help for information about the available features for the driver.

3. If printing on card stock, on the **Paper** tab or the **Paper/Quality** tab, select **Cardstock** from the **Type is:** drop-down list.
4. Print the document.

Printing on both sides of the media (manual duplexing)

To print on both sides of the media (manual duplexing), you must send the media through the device twice.

Manual duplexing can cause the device to become dirty, which reduces print quality. If the device becomes dirty, see Cleaning and maintenance for instructions.

To manually duplex

Note The printer driver also contains instructions and graphics for manually duplexing.

1. In the software program, open the device properties (printer driver). For instructions, see To change settings for a print job.
2. On the **Finishing** tab, select **Print on Both Sides**.

Note If the **Print on Both Sides** option is dimmed or unavailable, open the device properties (printer driver). For instructions, see To change default settings across all programs. On the **Device Settings** tab or the **Configure** tab, select **Allow Manual Duplexing**, and then click **OK**. Repeat steps 1 and 2.

3. Print the document.
4. After side one has been printed, remove the remaining media from the input tray, and set it aside until after you finish your manual duplexing job.



5. Gather the printed pages, keep the printed side facing down, and straighten the stack.



6. Place the stack of media in the input tray again. Side one should be facing down with the top edge feeding into the device first.



7. Click **OK** (on the computer screen), and then wait for side two to print.

Printing multiple pages on a single sheet of media

You can select the number of pages that you want to print on a single sheet of media. If you choose to print more than one page per sheet, the pages appear smaller and are arranged on the sheet in the order that they would otherwise be printed. You can specify up to 16 pages per sheet of media.



To print multiple pages on a single sheet

1. In the software program, open the device properties (printer driver). See Changing print settings for instructions.
2. On the **Finishing** tab under **Pages Per Sheet**, select the number of pages per sheet that you want to print.
3. Select the check box for page borders if you want the printed pages to have borders. Use the drop-down list to select the order in which pages are printed on the sheet.

Printing booklets

You can print booklets on letter, legal, or A4 print media.

To print booklets

1. Load the print media in the media input tray.



2. In the software program, open the device properties (printer driver). For instructions, see To change settings for a print job.
3. On the **Finishing** tab, select **Print on Both Sides**.

Note

If the **Print on Both Sides** option is dimmed or unavailable, open the device properties (printer driver). For instructions, see To change default settings across all programs. On the **Device Settings** tab or the **Configure** tab, select the option to allow manual duplexing, and then click **OK**. Repeat steps 2 and 3.

Not all device features are available for all printer drivers or operating systems. See the device properties (driver) online Help for information about the available features for the driver.

4. Set the number of pages per sheet to two. Select the appropriate binding option, and click **OK**.
5. Print the booklet.
6. After side one has been printed, remove the remaining paper from the media input tray, and set it aside until your booklet job is complete.



7. Gather the printed pages, turn the printed side down, and straighten the stack of paper.



8. Place the pages from side one in the input tray again. Side one should be facing down with the bottom edge feeding into the device first.



9. Click **OK** (on the computer screen), and wait for side two to print.
10. Fold and staple the pages.



Printing watermarks

You can use the watermark option to print text “underneath” (in the background) of an existing document. For example, you might want to have large gray letters that spell Draft or Confidential printed diagonally across the first page or all of the pages of a document.



To use the watermark feature

1. In the software program, open the device properties (printer driver). See Changing print settings for instructions.
2. On the **Effects** tab, use the drop-down list to select the watermark that you want to print on your document. To print the watermark on only the first page of the document, select the **First Page Only** check box.

4 Copying

Use these instructions to perform copying tasks with your device:

- Loading originals to copy
- Starting a copy job
- Canceling a copy job
- Adjusting the copy quality
- Adjusting the lighter/darker (contrast) setting
- Reducing or enlarging copies
- Changing the default copy-collation setting
- Changing the default number of copies
- Copying two-sided originals

Note Many of the functions that are described in this chapter also can be performed by using the HP toolbox. For instructions about using the HP toolbox, see Using the hp toolbox.

Loading originals to copy

Use these instructions to load originals into your device for copying. See Selecting media for the automatic document feeder (ADF) for information about choosing original documents for copying.

To load originals into the automatic document feeder (ADF) input tray

Note

ADF capacity is up to 30 sheets of 75 g/m^2 (20 lb) media (depending on the thickness of the media), or until the ADF input tray is full.

The minimum size for media in the ADF is 74 by 105 mm ((2.9 by 4.1 inches)). The maximum size for media in the ADF is 215 by 356 mm ((8.5 by 14 inches)). The ADF output bin holds one sheet of legal-size media (215 by 356 mm (8.5 by 14 inches)). Subsequent sheets of legal-size media slide off of the ADF output bin.

1. Adjust the ADF media lever, if necessary.

Note

Move the ADF media lever to the right (single-sheet setting) if you are printing on a single sheet of thick media.



2. Load the stack of originals to be copied into the automatic document feeder (ADF) with media stack face-down and the first page to be copied at the bottom of the stack.



3. Slide the media stack into the ADF until the media does not move any farther. You might have to tap the stack into the ADF.

4. Adjust the media guides until they are snug against the media.



5. The document is now ready to be copied.

CAUTION To prevent damaging the device, do not use an original that contains correction tape, correction fluid, or staples.

If you moved the ADF media lever to the right in step 1, move it back to the left when you have finished printing. Printing on regular media with the ADF media lever moved to the right can cause jams.

Starting a copy job

To make copies with your device, use the following instructions.

1. Load your original document face-down into the automatic document feeder (ADF) input tray.
2. Press START/COPY on the device control panel to start copying.
3. Repeat the process for each copy.

For more detailed instructions about loading originals into the ADF input tray, see Loading originals to copy.

Canceling a copy job

To cancel a copy job, press CANCEL on the device control panel. If more than one process is running, pressing CANCEL clears the process that currently appears on the device control panel display.

Note If you cancel a copy job, clear the original document from the automatic document feeder (ADF).

Adjusting the copy quality

The factory-set default for copy quality is **Text**. This setting is the best for items that contain mostly text.

When making a copy of a photo or graphic, you can select the **Photo** setting to increase the quality of your copy, or select the **Best Photo** setting for the highest photo quality.

If you want to conserve toner, and the copy quality is not as important, select **Draft**.

To adjust the copy quality for the current job

1. On the device control panel, press QUALITY to see the current quality setting for the copy.
2. Use the < or the > button to scroll through the quality setting options.
3. Select a resolution setting, and then press START/COPY to save the selection and immediately start the copy job, or press MENU/ENTER to save the selection without starting the job.

Note The change in the copy quality setting remains active for about two minutes after the copy job has been completed. During this time, **Settings=Custom** appears on the device control panel display.

To adjust the default copy quality

1. On the device control panel, press MENU/ENTER.
2. Use the < or the > button to select **Copy setup**, and then press MENU/ENTER.
3. Press MENU/ENTER to select **Default Quality**.
4. Use the < or the > button to scroll through the choices.
5. Press MENU/ENTER to save the selection.

Adjusting the lighter/darker (contrast) setting

The lighter/darker setting affects the lightness or darkness (contrast) of the copy. Use the following procedure to change the contrast for the current copy job only.

To adjust the lighter/darker setting for the current job

1. On the device control panel, press LIGHTER/DARKER to see the current contrast setting.
2. Use the < or the > button to adjust the setting. Move the slider to the left to make the copy lighter than the original, or move the slider to the right to make the copy darker than the original.
3. Press START/COPY to save the selection and immediately start the copy job, or press MENU/ENTER to save the selection without starting the job.

Note

The change in the setting remains active for about two minutes after the copy job has been completed. During this time, **Settings=Custom** appears on the device control panel display.

To adjust the default lighter/darker setting

1. On the device control panel, press MENU/ENTER.
2. Use the < or the > button to select **Copy setup**, and then press MENU/ENTER.
3. Use the < or the > button to select **Def. Light/Dark**, and then press MENU/ENTER.
4. Use the < or the > button to adjust the setting. Move the slider to the left to make all of the copies lighter than the original, or move the slider to the right to make all of the copies darker than the original.
5. Press MENU/ENTER to save the selection.

Reducing or enlarging copies

The device can reduce copies to as little as 25 percent of the original or enlarge copies to as much as 400 percent of the original. It can also make the following reductions or enlargements automatically:

Note You must change the default paper size in the media input tray to match the output size, or part of your copy might be cut off. For instructions, see Changing the default media size.

- **Original=100%**
- **Lgl > Ltr=78%**
- **Lgl > A4=83%**
- **A4 > Ltr=94%**
- **Ltr > A4=97%**
- **Full Page=91%**
- **2 pages/sheet**
- **4 pages/sheet**
- **Custom: 25-400%**

Note After selecting the **2 pages/sheet** or **4 pages/sheet** option, you must select the page orientation (portrait or landscape).

To reduce or enlarge copies for the current job

To reduce or enlarge copies for the current job only, use the following instructions.

1. On the device control panel, press REDUCE/ENLARGE.
2. Select the size to which you would like to reduce or enlarge the copies in this job. You can select:
   - **Original=100%**
   - **Lgl > Ltr=78%**
   - **Lgl > A4=83%**
   - **A4 > Ltr=94%**
   - **Ltr > A4=97%**
   - **Full Page=91%**
   - **2 pages/sheet**
   - **4 pages/sheet**
   - **Custom: 25-400%**

   If you select **Custom: 25-400%**, type a percentage by using the alphanumeric buttons.

   If you select **2 pages/sheet** or **4 pages/sheet**, select the orientation (portrait or landscape).
3. Press START/COPY to save the selection and immediately start the copy job, or press MENU/ENTER to save the selection without starting the job.

Note The change in the setting remains active for about two minutes after the copy job has been completed. During this time, **Settings=Custom** appears on the device control panel display.

To change the default copy size

The default copy size is the size to which copies are normally reduced or enlarged. If you keep the factory-default size setting of **Original=100%**, all copies will be the same size as the original document.

1. Press MENU/ENTER.
2. Use the < or the > button to select **Copy setup**, and then press MENU/ENTER.
3. Use the < or the > button to select **Def. Redu/Enlrg**, and then press MENU/ENTER.

4. Use the < or the > button to select the option for how you normally want to reduce or enlarge copies. You can select:
   - **Original=100%**
   - **Lgl > Ltr=78%**
   - **Lgl > A4=83%**
   - **A4 > Ltr=94%**
   - **Ltr > A4=97%**
   - **Full Page=91%**
   - **2 pages/sheet**
   - **4 pages/sheet**
   - **Custom: 25-400%**

   If you select **Custom: 25-400%**, type in the percentage of the original size that you normally want for copies.

   If you select **2 pages/sheet** or **4 pages/sheet**, select the orientation (portrait or landscape).
5. Press MENU/ENTER to save your selection.

Changing the default copy-collation setting

You can set the device to automatically collate multiple copies into sets. For example, if you are making two copies of three pages and the automatic collation is on, the pages print in this order: 1,2,3,1,2,3. If automatic collation is off, the pages print in this order: 1,1,2,2,3,3.

To use the automatic collation, the original document must fit into the memory. If it does not, the device makes only one copy and a message appears notifying you of the change. If that happens, use one of the following methods to finish the job:

- Split the job into smaller jobs that contain fewer pages.
- Make only one copy of the document at a time.
- Turn off the automatic collation.
- If using the **Best Photo** quality setting, try using the **Photo** setting instead.

The collation setting you select is in effect for all copies until you change the setting.

The collation setting can also be changed from the device software. For instructions about changing settings from the device software, see Changing print settings.

To change the default copy-collation setting

1. On the device control panel, press MENU/ENTER.
2. Use the < or the > button to select **Copy setup**, and then press MENU/ENTER.
3. Press MENU/ENTER to select **Def. Collation**.
4. Use the < or the > button to select **On** or **Off**.
5. Press MENU/ENTER to save your selection.

Note The factory-set default for automatic copy collation is **On**.

Changing the default number of copies

You can choose to have the default number of copies be any number from 1 to 99.

To change the default number of copies

1. On the device control panel, press MENU/ENTER.
2. Use the < or the > button to select **Copy setup**, and then press MENU/ENTER.
3. Use the < or the > button to select **Def. # of copies**, and then press MENU/ENTER.
4. Use the alphanumeric buttons to type the number of copies (between 1 and 99) that you want as the default.
5. Press MENU/ENTER to save your selection.

Note The factory-set default for the number of copies is **1**.

Copying two-sided originals

To copy a multiple-page stack of two-sided originals

1. Load the stack of originals to be copied into the automatic document feeder (ADF) input tray with the first page facing down, and with the top of the page leading into the ADF.



2. Press START/COPY. The odd-numbered pages are copied and printed.
3. Remove the stack from the ADF output tray and reload the stack with the last page facing down, and with the top of the page leading into the ADF.



4. Press START/COPY. The even-numbered pages are copied and printed.
5. Collate the odd- and even-numbered printed copies.



5 Scanning

Use the following instructions to perform scanning tasks:

- Loading originals to scan
- Understanding scanning methods
- Canceling a scan job
- Scanning from the device control panel
- Scanning by using hp LaserJet Scan software
- Scanning by using TWAIN-compliant and WIA-compliant software
- Scanning by using OCR
- Scanner resolution and color

Loading originals to scan

Use these instructions to load originals into the device for scanning. See Selecting media for the automatic document feeder (ADF) for information about choosing original documents for scanning.

Loading originals into the automatic document feeder (ADF) input tray

Note

Automatic document feeder (ADF) capacity is up to 30 sheets of 75 g/m^2 (20 lb) media (depending on the thickness of the media), or until the ADF input tray is full.

The minimum size for media in the ADF input tray is 74 by 105 mm (2.9 by 4.1 inches). The maximum size for media in the ADF input tray is 215 by 356 mm (8.5 by 14 inches).

1. Adjust the ADF media lever, if necessary.

Note

Move the ADF media lever to the right (single-sheet setting) if you are printing on a single sheet of thick media.



2. Put the top end of the original media stack into the ADF input tray, with the media stack face down and the first page to be scanned at the bottom of the stack.



3. Slide the media stack into the ADF until the media does not move any farther. You might have to tap the stack into the ADF.
4. Adjust the media guides until they are snug.



5. The document is now ready to be scanned.

CAUTION To prevent damaging the device, do not use an original that has correction fluid, correction tape, or staples.

If you moved the ADF media lever to the right in step 1, move it back to the left when you have finished printing. Printing on regular media with the ADF media lever moved to the right can cause jams.

Understanding scanning methods

You can scan an item in the following ways.

- **Scan from the device:** Start scanning directly from the device by using the device control panel scan buttons. The SCAN TO button can be programmed to scan to e-mail or to scan to a folder. For more information, see Scanning from the device control panel.
- **Scan from hp LaserJet Scan software:** Press START SCAN on the device control panel to start the HP LaserJet Scan program. Pressing START SCAN to start the HP LaserJet Scan software is not supported when the device is connected to a network. (Direct-connect only.) You can also start HP LaserJet Scan software directly from the computer. For more information, see Scanning by using hp LaserJet Scan software.

Note HP LaserJet Scan software is not supported for networked connections.

- **Scan from TWAIN-compliant or WIA-compliant software:** The device is TWAIN-compliant and WIA-compliant and works with Windows-based programs that support TWAIN-compliant or WIA-compliant scanning devices. The device scanning software is also TWAIN-compliant and WIA-compliant. For more information, see Scanning by using TWAIN-compliant and WIA-compliant software.

Note To learn about and use optical character recognition (OCR) software, install the Readiris program from the software CD-ROM.

Canceling a scan job

To cancel a scan job, use one of the following procedures.

- Press CANCEL on the device control panel.
- Click the **Cancel** button in the onscreen dialog box.

If you cancel a scan job, remove the original document from the automatic document feeder (ADF) input tray.

Scanning from the device control panel

Use the following instructions to scan directly from the device control panel.

Note The computer that is connected to the device must be turned on.

Programming the Scan to button

To program the device SCAN TO button, you must gain access to the device settings. Go to the **Scan** section of the HP toolbox and click the **Scan to...** tab. For more information, see the HP toolbox Help.

Scanning to e-mail

To scan to e-mail by using the SCAN TO button on the device control panel, use the following procedure:

Note To use this feature, an e-mail recipient must be programmed in the **Scan to...** tab. See Programming the Scan to button.

1. Load the originals that are to be scanned face-down in the automatic document feeder (ADF) input tray, with the top of the document leading into the device. Adjust the media guides to hold the originals in place.
2. Press SCAN TO on the device control panel.
3. Use the < or the > button to select an e-mail recipient.
4. Press START SCAN or MENU/ENTER. The scanned item is attached to an e-mail message, which is then sent automatically to the e-mail recipient that you selected in step 3.

Scanning to a folder

To scan to a folder by using the SCAN TO button on the device control panel, use the following instructions.

Note To use this feature, a folder must be set up in the **Scan to...** tab prior to use. See Programming the Scan to button.

1. Load the originals that are to be scanned face-down in the automatic document feeder (ADF) input tray, with the top of the document forward, and adjust the media guides.
2. Press SCAN TO on the device control panel.
3. Use the < or the > button to select a folder.
4. Press START SCAN or MENU/ENTER. The document is scanned to a file, which is then saved in the folder that you selected in step 3.

Scanning by using hp LaserJet Scan software

Use the HP LaserJet Scan software program to scan an item to any of the following:

- e-mail
- a folder
- another software program that you specify
- the Readiris OCR program, if it is installed on the computer

For more detailed instructions about loading original documents into the automatic document feeder (ADF), see Loading originals to scan.

Scanning to e-mail

1. Adjust the automatic document feeder (ADF) media lever to accommodate either a single sheet or a stack of media. (For more information, see Loading originals to scan.
2. Load the originals that are to be scanned face-down in the ADF, with the top of the document leading into the device. Adjust the media guides to hold the originals in place.
3. On the computer, click **Start**, select **Hewlett-Packard**, select **hp LaserJet 3015**, and then select **Scan**.

   OR

   Press START SCAN on the device. HP LaserJet Scan software opens on the computer. Pressing START SCAN to start the HP LaserJet Scan software is not supported when the device is connected to a network. (Direct-connect only.)
4. In the HP LaserJet Scan dialog box, select **Send it through e-mail**.
5. Click **Settings**.
6. Set the scanning options that you want, and then click **OK** to return to the HP LaserJet Scan dialog box.

Note You can save the settings using the **Quick Sets** option on the **General** tab. If you then select the check box after saving a Quick Set, the saved settings will be the default settings the next time you scan to e-mail.

7. Click **Scan**. The original is scanned, attached to a new e-mail message, and sent automatically.

Note If no e-mail recipient is entered on the **E-mail** tab, the original is scanned and attached to a new e-mail message, but is not sent. You can then enter an e-mail recipient, add text or other attachments, and then send the message.

The options that you set in step 6 are for the current job only, unless you save them as a Quick Set.

To scan to a file

1. Adjust the automatic document feeder (ADF) media lever to accommodate either a single sheet or a stack of media. (For more information, see Loading originals to scan.
2. Load the originals that are to be scanned face-down in the ADF, with the top of the document leading into the device. Adjust the media guides to hold the originals in place.

3. On the computer, click **Start**, select **Hewlett-Packard**, select **hp LaserJet 3015**, and then select **Scan**.

   OR

   Press START SCAN on the device. HP LaserJet Scan software opens on the computer. Pressing START SCAN to start the HP LaserJet Scan software is not supported when the device is connected to a network. (Direct-connect only.)

4. In the HP LaserJet Scan dialog box, select **Send it to a file**.
5. Click **Settings**.
6. Set the scanning options that you want, and then click **OK** to return to the HP LaserJet Scan dialog box.

Note You can save the settings using the **Quick Sets** option on the **General** tab. If you then select the check box after saving a Quick Set, the saved settings will be the default settings the next time you scan to a file.

7. Click **Scan**. If prompted, enter a file name.

Note The options that you set in step 6 are for the current job only, unless you save them as a Quick Set.

Scanning to another software program

Scanning to another software program allows you to scan to a program that is not TWAIN-compliant or WIA-compliant.

1. Adjust the automatic document feeder (ADF) media lever to accommodate either a single sheet or a stack of media. (For more information, see Loading originals to scan.
2. Load the originals that are to be scanned face-down in the ADF, with the top of the document leading into the device. Adjust the media guides to hold the originals in place.
3. On the computer, click **Start**, select **Hewlett-Packard**, select **hp LaserJet 3015**, and then select **Scan**.

   OR

   Press START SCAN on the device. HP LaserJet Scan software opens on the computer. Pressing START SCAN to start the HP LaserJet Scan software is not supported when the device is connected to a network. (Direct-connect only.)

4. In the HP LaserJet Scan dialog box, select **Send it to another software application**.
5. Click **Settings**.
6. Set the options that you want. On the **Other Applications** tab, click **Browse** to locate the program's executable file, which has the file extension ".exe." You can also type the location of the executable file.

Note You can save the settings using the **Quick Sets** option on the **General** tab. If you then select the check box after saving a Quick Set, the saved settings will be the default settings the next time you scan to another software program.

7. Select the file type supported by this program.
8. Click **OK** to return to the HP LaserJet Scan dialog box.
9. Click **Scan**.

Note The options that you set in step 6 are for the current job only, unless you save them as a Quick Set.

Scanning to the Readiris OCR software

1. Adjust the automatic document feeder (ADF) media lever to accommodate either a single sheet or a stack of media. (For more information, see Loading originals to scan.
2. Load the originals that are to be scanned face-down in the automatic document feeder (ADF) input tray, with the top of the document leading into the device. Adjust the media guides to hold the originals in place.
3. On the computer, click **Start**, select **Hewlett-Packard**, select **hp LaserJet 3015**, and then select **Scan**.

   OR

   Press START SCAN on the device. HP LaserJet Scan software opens on the computer. Pressing START SCAN to start the HP LaserJet Scan software is not supported when the device is connected to a network. (Direct-connect only.)
4. In the HP LaserJet Scan dialog box, select **Send it to the Readiris OCR software**.
5. Click **Scan**.

Note Readiris must be installed on the computer before the device can scan to the Readiris OCR program. The software CD-ROM that came with the device includes the Readiris OCR program.

Scanning by using TWAIN-compliant and WIA-compliant software

The device is TWAIN-compliant and Windows Imaging Application (WIA)-compliant. The device works with Windows-based programs that support TWAIN-compliant or WIA-compliant scanning devices.

Note If the software program you are using is not TWAIN-compliant or WIA-compliant, see Scanning to another software program.

Using TWAIN-compliant and WIA-compliant software

While you are in a TWAIN-enabled or WIA-enabled program, you can gain access to the scanning feature and scan an image directly into the open program. For more information, see the Help file or the documentation that came with your TWAIN-compliant or WIA-compliant software program.

Scanning from a TWAIN-enabled program

Generally, a software program is TWAIN-enabled if it has a command such as **Acquire**, **File Acquire**, **Scan**, **Import New Object**, **Insert from**, or **Scanner**. If you are unsure whether the program is compliant or you do not know what the command is called, see the software program Help or documentation.

When scanning from a TWAIN-enabled program, the HP LaserJet Scan software might start automatically. If the HP LaserJet Scan software starts, you can make changes while you are previewing the image. If the program does not start automatically, the image goes to the TWAIN-enabled program immediately.

To scan from a TWAIN-enabled program

Start the scan from within the TWAIN-enabled program. See the software program Help or documentation for information about the commands and steps to use.

Scanning from a WIA-enabled program (Windows XP only)

WIA is another way to scan an image directly into a software program, such as Microsoft® Word. WIA uses Microsoft software to scan, instead of HP LaserJet Scan software.

Generally, a software program is WIA-enabled if it has a command such as **Picture/From Scanner or Camera** in the Insert or File menu. If you are unsure whether the program is WIA-enabled, see the software program Help or documentation.

To scan from a WIA-enabled program

Start the scan from within the WIA-enabled program. See the software program Help or documentation for information about the commands and steps to use.

OR

In the Cameras and Scanner folder, double-click the device icon. This opens the standard WIA-enabled software program, which enables you to scan to a file.

Scanning by using OCR

You can use OCR software to import scanned text into your preferred word-processing program for editing.

Readiris

The software CD-ROM includes the Readiris OCR program. If you want to use the Readiris program, install it from the software CD-ROM, and then follow the instructions in the online Help.

Scanner resolution and color

If you are printing a scanned image, and the quality is not what you expected, you might have selected a resolution or color setting in the scanner software that does not match your needs. Resolution and color affect the following features of scanned images:

- Image clarity
- Texture of gradations (smooth or rough)
- Scan time
- File size

Resolution is measured in dots per inch (dpi). Color, grayscale, and black and white define the number of colors possible. You can adjust the scanner hardware resolution to up to 600 dpi. The software can perform an enhanced resolution up to 9,600 dpi. You can set color and grayscale at 1 bit (black and white), or at 8 bit (256 levels of gray) to 24 bit (true color).

The resolution and color guidelines table lists simple tips that you can follow to meet your scanning needs.

Note Setting the resolution and color to a high value can create large files that take up disk space and slow the scanning process. Before setting the resolution and color, determine how you are going to use the scanned image.

Resolution and color guidelines

The following table describes the recommended resolution and color settings for different types of scan jobs.

Intended use	Recommended resolution	Recommended color settings
Fax	150 dpi	• Black and White
E-mail	150 dpi	• Black and White, if the image does not require smooth gradation • Grayscale, if the image requires smooth gradation • Color, if the image is in color
Edit text	300 dpi	• Black and White
Print (graphics or text)	600 dpi for complex graphics, or if you want to significantly enlarge the document 300 dpi for normal graphics and text 150 dpi for photos	• Black and White for text and line art • Grayscale for shaded or colored graphics and photos • Color, if the image is in color
Display on screen	75 dpi	• Black and White for text • Grayscale for graphics and photos • Color, if the image is in color

Color

You can set the color values to the following settings when scanning.

Setting	Recommended use
Color	Use this setting for high-quality color photos or documents in which the color is important.
Black and White	Use this setting for text documents.
Grayscale	Use this setting when file size is an issue or when you want a document or photograph to be scanned quickly.

6 Faxing

For instructions about using the device fax functionality, see the fax guide that came with the device.

7 Cleaning and maintenance

Use the topics below to learn about basic cleaning and maintenance tasks:

- Cleaning the outside of the device
- Cleaning the media path

Cleaning the outside of the device

To clean the exterior

Use a soft, damp, lint-free cloth to wipe dust, smudges, and stains off the exterior of the device.

To clean the glass

Over time, specks of debris might collect on the scanner glass and affect performance. Use the following procedure to clean the scanner glass.

1. Turn off the device, and unplug the power cord from the electrical socket.
2. Tilt the device control panel forward.
3. Clean the glass strip with a soft cloth or sponge that has been moistened with nonabrasive glass cleaner.



CAUTION Do not use abrasives, acetone, benzene, ammonia, ethyl alcohol, or carbon tetrachloride on any part of the device; these can damage the device. Do not place liquids directly on the glass. They might seep under it and damage the device.

4. Dry the glass with a chamois or cellulose sponge to prevent spotting.

Cleaning the media path

If you are experiencing toner specks or dots on the printouts, clean the media path.

To clean the media path

1. Press MENU/ENTER.
2. Use the < or the > button to find the **Service** menu.
3. Press MENU/ENTER.
4. Use the < or the > button to find **Cleaning Mode**.
5. Press MENU/ENTER.

8 Troubleshooting

Use this section to find tips for solving problems with the device:

- Device does not turn on
- The device control panel display has black lines or dots, or fades
- Pages print but are totally blank
- Pages did not print
- Pages printed, but a problem exists
- Onscreen error messages appear
- Paper-handling problems exist
- Printed page is different from what appears onscreen
- Media jams occur in the printer
- Print quality is unacceptable
- Device control panel error messages appear
- No copy came out
- Copies are blank, or images are missing or faded
- Copy quality is unacceptable
- Media jams occur in the automatic document feeder (ADF)
- Copy defects are apparent
- Scanned image is of poor quality
- Part of the image did not scan
- The scan takes too long
- Error messages appear
- Scan quality is unacceptable

Note Many of the functions that are described in this chapter also can be performed by using the HP toolbox. For instructions about using the HP toolbox, see Changing the settings by using the hp toolbox or the device control panel.

Device does not turn on

Try the tips in this section if the device does not turn on.

Is power reaching the device?

- If you are using a power strip, make sure that the power strip is turned on. Or, try plugging the device directly into the power outlet.
- Test the power outlet to make sure that it is working.
- If you have plugged the device into a switched outlet, make sure that the switch is on.
- Make sure that the power switch on the back of the device is turned on.

WARNING! If the problem persists after you try the preceding remedies, the device might be experiencing a mechanical failure. Unplug the device from the power outlet and contact HP. See the support flyer that came with the device for information about contacting HP.

The device control panel display has black lines or dots, or fades

Try the tips in this section if the device control panel display has black lines or dots, or fades.

Black lines or dots

CAUTION Static electricity can cause unexpected black lines or dots to appear on the device control panel display. Do not touch the device control panel display if there is a chance that you have collected a static electric charge (for example, by walking on carpet in a low-humidity environment).

Unexpected lines or dots might appear on the device control panel display if the device control panel display is exposed to a static electric charge. Wait until the black lines or dots fade away (usually within a few minutes).

Note Do not print while the black lines or dots are visible.

Do not turn the device off and on. This does not solve the problem.

Faded device control panel display

CAUTION Magnets or strong electric fields can cause the device control panel display to fade. Do not place the device near magnets or strong electric fields.

The device control panel display might fade if the device is exposed to magnets or strong electric fields. Move the device away from the magnets or strong electric fields, and wait until the device control panel display returns to normal (usually within a few minutes).

Note Do not print while the device control panel display is faded.

Do not turn the device off and on unless you are moving it to a different location. This does not solve the problem.

Pages print but are totally blank

Try the tips in this section if pages exit the device, but have nothing printed on them.

Is the sealing tape still in the print cartridge?

The sealing tape might still be in the print cartridge. Remove the print cartridge and pull out the sealing tape. Reinstall the print cartridge. Try printing the document again.

Does the configuration page print?

To check the device, print a configuration page. See Printing a configuration page for instructions.

Does the document contain blank pages?

The document might contain blank pages. Check the document that you are printing to see if content appears on all of the pages.

Is the original loaded correctly?

If you are making a copy, the original might be loaded incorrectly. The original must be loaded into the automatic document feeder (ADF) with the print-side facing down. If the original is loaded print-side up, the copy prints out blank.

Pages did not print

Try these tips when the device does not print any pages.

Does a message appear on your computer screen?

See Onscreen error messages appear for more information.

Is media being pulled into the device correctly?

See Paper-handling problems exist for more information.

Are media jams present?

See Media jams occur in the automatic document feeder (ADF) or Media jams occur in the printer for more information.

Is the parallel or USB Device Cable (A/B) working, and is it connected correctly?

The parallel or USB Device Cable (A/B) might be defective. Try the following remedies:

- Disconnect the parallel or USB Device Cable (A/B) at both ends and reconnect it.
- Try printing a job that has printed in the past.
- Try using a different IEEE 1284-B-compliant parallel cable or USB Device Cable (A/B). See Ordering HP parts and accessories.
- Contact the manufacturer of your computer about changing parallel port settings to an extended capabilities port (ECP) mode.

Are other devices running on your computer?

- The device might not share a parallel port. If you have an external hard drive or network switchbox that is connected to the same port as the device, the other device might be interfering. To connect and use the device, you must disconnect the other device or you must use two parallel ports on the computer.
- You might need to add another interface card. Hewlett-Packard strongly recommends an ECP parallel interface card.

Pages printed, but a problem exists

Try these tips when pages are printed on, but a problem exists.

Is the print quality poor?

See Print quality is unacceptable for more information.

Is the printed page different from what appears onscreen?

See Printed page is different from what appears onscreen for more information.

Are the device settings appropriate for the print media?

See Paper-handling problems exist for more information.

Onscreen error messages appear

If the following messages appear onscreen, use the appropriate procedures to remedy the problem.

Printer not responding/error writing to LPT1

Check the following conditions:

- Is the device in the **Ready** state?
- Are the power cord and the IEEE 1284-B-compliant parallel or USB Device Cable (A/B) correctly connected?
- Are other printer drivers installed on the computer?

Try the following remedies:

- Disconnect the power cord and IEEE 1284-B-compliant parallel or USB Device Cable (A/B) at both ends and reconnect them.
- Use another IEEE 1284-B-compliant parallel or USB Device Cable (A/B).
- Make sure that another device or printer is not selected as the default printer.

Cannot access port (in use by another application)

A device conflict exists. This might occur if another device is installed on your computer and is running status software. The status software dominates the parallel port on the computer and denies the device access to the port.

Try the following remedies:

- Disable all of the status windows for other devices.
- Make sure that the device port setting is correct. Change the port settings on the **Details** tab or the **Ports** tab in the device properties.
- Make sure that bidirectional support is disabled for the device. On the **Details** tab or the **Ports** tab in the device properties, make sure that the bidirectional support option is *not* selected.

Note In some operating systems, you must click **Spool Settings** on the **Details** tab in order to see the bidirectional support option.

Paper-handling problems exist

Use the tips in this section when the device experiences paper-handling problems.

Print is skewed (crooked)

Are the media guides adjusted properly?

Remove all media from the input tray, straighten the stack, and then load the media in the input tray again. Adjust the media guides to the width and length of the media that you are using and try printing again. See Device media specifications or the start guide for more information.

More than one sheet feeds at one time

Is the media input tray too full?

See the start guide for more information about loading media input trays.

Is the media wrinkled, folded, or damaged?

Make sure the media is not wrinkled, folded, or damaged. Try printing on media from a new or different package.

Is the automatic document feeder (ADF) media lever set incorrectly?

Make sure the ADF media lever is set to the multiple-sheet setting (to the left).

Device does not pull media from the media input tray

Is the device in manual feed mode?

Try one of the following remedies:

- If **Manual feed** appears on the device control panel display, press MENU/ENTER to print the job.
- Make sure that the device is not in manual feed mode and print your job again.

Is the pickup roller dirty or damaged?

Contact a local HP authorized service provider. See Service and support for instructions.

Media curls when fed through device

See Curl or wave for more information.

Printed page is different from what appears onscreen

Try the tips in this section when what is printed on the page differs from what appears onscreen.

Is the text garbled, incorrect, or incomplete?

To verify that the device is functioning, print a configuration page . See Printing a configuration page for instructions. If the configuration page prints successfully, try the following remedies:

- Disconnect the cable and reconnect it at both ends.
- Try printing a job that has printed correctly in the past.
- If possible, attach the cable and device to another computer, and then try printing a job that you know has printed correctly.
- Try using a new IEEE 1284-B-compliant parallel or USB Device Cable (A/B). See Ordering HP parts and accessories for information.
- The wrong printer driver might have been selected when the device software was installed. Make sure that the device is selected in the device properties.
- The software program might be experiencing a problem. Try printing from another software program.

Are graphics or text missing? Are there blank pages?

- If the software progam you are using has a Print Preview option, can you see the missing graphics or text in the Print Preview screen?
- Make sure that the document does not contain blank pages.
- The sealing tape might still be in the print cartridge. Remove the print cartridge, and pull out the sealing tape.
- Reinstall the print cartridge. See the start guide for more information about print cartridges.
- To check the device, print a configuration page. See Printing a configuration page for instructions.
- The graphic settings in the device properties might not be correct for the type of job that you are printing. Try a different graphic setting in the device properties. See Changing print settings for more information.
- The printer driver might not work for the type of job that you are printing. Try using a different printer driver.

Note If you use a different printer driver, some device features might not be available.

Is the page format different from the format on another printer?

If you used an older or different printer driver (printer software) to create the document or the device properties settings in the software are different, the page format might change when you try to print using your new printer driver or settings. To help eliminate this problem, try the following remedies:

- Create documents and print them using the same printer driver (printer software) and device properties settings regardless of which device you use to print the documents.
- Change the resolution, media size, font settings, and other settings. See Changing print settings for more information.

Is the quality of the graphics poor?

The graphics settings might be unsuitable for your print job. Try the following remedies:

- Check the graphic settings, such as resolution, in the device properties and adjust them as necessary. See Changing print settings for more information.
- Try using a different printer driver (printer software).

Note If you use a different printer driver, some device features might not be available.

Media jams occur in the printer

Occasionally, media becomes jammed during a print job. Try the following remedies before you attempt to clear the jam:

- Make sure that you are printing on media that meets HP specifications. See Device media specifications for more information.
- Make sure that you are printing on media that is not wrinkled, folded, or damaged.
- Make sure that the device is clean. See Cleaning the media path for more information.
- Make sure that the input trays are loaded properly and are not too full. See the start guide for more information about loading input trays.

Note When you add new media, always remove all of the media from the input tray and straighten the stack of new media. This helps prevent multiple sheets of media from feeding through the device at one time, which reduces media jams.

You are notified of a media jam by an error in the software program and a jam message on the device control panel display. See Device control panel error messages appear for more information.

CAUTION It is not necessary to remove the media input tray to clear a media jam. Remove the media input tray only to return the device for hardware service. For information about removing the media input tray, see To remove the media input tray.

To clear a media jam

CAUTION Media jams might result in loose toner on the page. If you get any toner on your clothes, wash them in cold water. Hot water will permanently set the toner into the fabric. If you get any toner on your hands, wash them in cold water.

Do not use a sharp object, such as a pencil or scissors, to remove jammed media.

Note When clearing jams, including jams in the output bin, always push the print-cartridge-door release to open the top cover, and remove the print cartridge. Keep the top cover open and the cartridge out until the jam has been cleared. Opening the top cover and removing the print cartridge relieves tension on the printer rollers, which makes removing jammed pages easier.

1. Push the print-cartridge-door release and open the top cover.



2. Grasp the handle of the print cartridge and remove it. Set it aside.



CAUTION To prevent damage to the print cartridge, do not expose it to light any longer than necessary. Place the print cartridge in a paper bag or other opaque container until you can place it back in the device.

3. With both hands, grasp the side of the media that is most visible (this includes the middle), and carefully pull it free from the device.



4. When you have removed the jammed media, replace the print cartridge.



5. Press the supporting springs, and close the top cover.

6. Open the media input tray and remove any media.



7. Slide the media guides inward as far as they will go. Press and hold down the tabs inside the media input tray, and slide the media input tray out of the device.



8. With both hands, grasp the side of the media that is most visible (this includes the middle), and carefully pull it free from the device.
9. Replace the input tray into the device.



10. After clearing the media jam, you might need to turn the device off, and then turn it on again.

Note When you add new media, remove all of the media from the input tray, straighten the stack of media after adding the new media, and then place the stack in the tray.

To clear other media jams

CAUTION Do not use a sharp object, such as a pencil or scissors, to remove jammed media.

If the media has jammed where it exits the device, grasp the leading edge of the media and pull the media out through the output bin.



Note

If you turned the device off before clearing the media jam, turn it on again, and then restart your printing or copying job.

If the media has jammed in the automatic document feeder (ADF), see Media jams occur in the automatic document feeder (ADF).

Tips to avoid media jams

- Make sure the automatic document feeder (ADF) media lever is in the correct position for the media you are using. Slide it to the single-sheet setting (to the right) when you are printing on thick media. Slide it to the multiple-sheet setting (to the left) when you are printing on regular media. For more information, see Loading originals to copy or Loading originals to scan.
- Make sure that the input tray is not overfilled. The input tray capacity varies depending on the type of print media that you are using.
- Check that the input tray is securely in place.
- Do not add print media into the input tray while the device is printing.
- Use only HP-recommended media types. See Device media specifications for more information about print media types.
- Do not let print media stack up in the output bin. The print media type and the amount of toner used affect the output bin capacity.
- Check the power connection. Make sure that the power cord is firmly connected to both the device and the power supply box. Plug the power cord into a grounded AC power outlet.

Print quality is unacceptable

This section provides information about identifying and correcting print defects.

Note

Hewlett-Packard does not recommend the use of uninterrupted power supply (UPS) battery-backup devices or surge suppressors with this device. Many surge suppressors and battery-backups can cause print defects.

Light print or fade



- The toner supply is low. See HP LaserJet print cartridges for more information.
- The media might not meet Hewlett-Packard media specifications (for example, the media is too moist or too rough). See Device media specifications for more information. If the whole page is light, the print density adjustment is too light or EconoMode might be turned on. Adjust the print density and turn off EconoMode in the device properties. See Saving toner for more information.

Toner specks



- The media might not meet Hewlett-Packard media specifications (for example, the media is too moist or too rough). See Device media specifications for more information.
- The device might need to be cleaned. See Cleaning the media path for instructions.

Dropouts



- A single sheet of media might be defective. Try reprinting the job.
- The moisture content of the media is uneven or the media has moist spots on the surface. Try printing on different media. See Device media specifications for more information.
- The media lot is bad. The manufacturing processes can cause some areas to reject toner. Try a different type of media.
- The print cartridge might be defective. See HP LaserJet print cartridges for more information.
- Check **Type is:** on the **Paper** tab or the **Paper/Quality** tab of the printer driver, and make sure that it is set to the appropriate media. See Optimizing print quality for media types for more information.

Note

If these steps do not correct the problem, contact an HP-authorized dealer or service representative. See the support flyer that came with your device for information about contacting HP.

Vertical lines



- Make sure that the priority input slot is in place.
- The photosensitive drum inside the print cartridge might be scratched. Try installing a new HP print cartridge. See the start guide for instructions.

Gray background



- Make sure that the priority input slot is in place.
- Decrease the print density setting by using the HP toolbox. This decreases the amount of background shading. See the device software Help for more information.
- Change the media to a lighter basis weight. See Device media specifications for more information.
- Check the device environment. Very dry (low humidity) conditions can increase the amount of background shading.
- Install a new HP print cartridge. See the start guide for instructions.

Toner smear



- The fuser temperature might be too low. Check **Type is:** on the **Paper** tab or the **Paper/ Quality** tab of the printer driver, and make sure that it is set to the appropriate media. See Optimizing print quality for media types for more information.
- If toner smears appear on the leading edge of the media, the media guides might be dirty. Wipe the media guides with a dry, lint-free cloth. See Cleaning the media path for more information.
- Check the media type and quality.
- Try installing a new HP print cartridge. See the start guide for instructions.

Loose toner



- Select **Type is:** on the **Paper** tab or the **Paper/Quality** tab of the printer driver, and select the media that you are using. See Optimizing print quality for media types for instructions. This feature is also available in the HP toolbox.
- Clean the inside of the device. See Cleaning and maintenance for instructions.
- Check the media type and quality. See Device media specifications for more information.
- Try installing a new HP print cartridge. See the start guide for instructions.
- Plug the device directly into an alternating current (AC) outlet instead of into a power strip.

Vertical repetitive defects

- The print cartridge might be damaged. If a repetitive mark occurs at the same spot on the page, install a new HP print cartridge. See the start guide for instructions.
- The internal parts might have toner on them. See Cleaning and maintenance for more information. If the defects occur on the back of the page, the problem will probably correct itself after a few more pages are printed.
- Select **Type is:** on the **Paper** tab or the **Paper/Quality** tab of the printer driver, and select the media that you are using. See Optimizing print quality for media types for more information. This feature is also available in the HP toolbox.

Misformed characters



- If characters are improperly formed, producing hollow images, the print media that you are using might be too slick. Try a different media. See Device media specifications for more information.
- If characters are improperly formed, producing a wavy effect, the device might need service. Print a configuration page. See Printing a configuration page for more information.
- If the characters are improperly formed, contact an HP-authorized dealer or service representative. See the support flyer that came with your device for more information about contacting HP.

Page skew



- Make sure that the media is loaded correctly and that the media guides are not too tight or too loose against the media stack. See the start guide for information about loading input trays.
- The automatic document feeder (ADF) input tray might be too full. See the start guide for information about loading input trays.
- Check the media type and quality. See Device media specifications for more information.

Curl or wave



- Check the media type and quality. Both high temperature and humidity can cause media to curl. See Device media specifications for more information.
- The media might have been in the input tray for a long time. Turn over the stack of media in the input tray. Also, try rotating the media 180° in the input tray.
- The fuser temperature might be too high. See Optimizing print quality for media types for instructions. This feature is also available in the HP toolbox.

You can also adjust the fuser temperature using the device control panel. The **Less paper curl** setting in the **Service** menu sets the fuser temperature to the lowest setting. The factory-set default is **Off**. Use the following instructions to turn this setting on.

1. On the device control panel, press MENU/ENTER.
2. Use the < or the > button to select **Service**, and then press MENU/ENTER.
3. Use the < or the > button to select **Less paper curl**, and then press MENU/ENTER.

Wrinkles or creases



- Make sure that the media is loaded properly. See the start guide for information about loading input trays.
- Check the media type and quality. See Device media specifications for more information.
- Turn over the stack of media in the tray. Also, try rotating the media 180° in the input tray.

Toner scatter outline



- If large amounts of toner have scattered around the characters, the media might be resisting the toner. (A small amount of toner scatter is normal for laser printing.) Try a different media type. See Device media specifications for more information.
- Turn over the stack of media in the tray.
- Use media that is designed for laser printers. See Device media specifications for more information.

Device control panel error messages appear

This section contains information about error messages that can appear on the device control panel display, and how to clear them.

Resolving common error messages

The following messages are the most common error messages that can appear on the device control panel display.

Door open or no print cartridge

The print cartridge door is open or no print cartridge has been installed. Make sure that you have correctly installed the print cartridge in the device. For information about installing the print cartridge, see the start guide.

After you have checked the print cartridge, close the print cartridge door securely.

When the problem is solved, the device either completes the current job or returns to the **Ready** state.

Add paper. [enter] to continue

The device is out of print media. Load media into the media input tray or the priority input slot. For information about loading media into the input trays, see the start guide.

If media is already loaded, remove the stack of media, check for and clear any media jams, and reload the input tray.

When the problem is solved, press MENU/ENTER. The device either completes the current job or returns to the **Ready** state.

Critical error messages

When a critical error occurs, the current copying or scanning job stops and one of the following messages appears on the device control panel:

- **50 Fuser Error**
- **51 Laser Error**
- **52 Scanner Error**
- **57 Fan Error**
- **79 Error**
- **CIS Scanner**

  Error
- **Scanner Bulb**

  failure

If one of these messages appears on the device control panel display, the device is experiencing a critical device error. Unplug the device for five minutes, and then plug it back in. If the error persists, contact HP customer service at the number provided on the support flyer included with the device, or visit http://www.hp.com.

Alert messages

Alert messages indicate that some action must be performed, such as adding print media or clearing a jam. When an alert message appears, the device automatically stops the current task and the job does not proceed until someone attends to the situation. After you correct the error, the device either completes the task or returns to the **Ready** state. The exception to this is when you want to use the main menus system. Then the device changes the display so that you can use the menus system.

The following messages are generic alert messages that might appear on the device control panel display:

- **Doc feeder jam**

  Clear, Reload
- **Document feeder**

  mispick. Reload
- **Door open or no**

  print cartridge
- **Manual feed**

  Press [enter]
- **Memory is low**

  Press [enter]
- **Add paper.**

  [enter] to continue
- **No print**

  cartridge
- **Printer jam**

  Clear paper path

Note

See Media jams occur in the automatic document feeder (ADF) or Media jams occur in the printer for more information about media jams.

Warning messages

Warning messages are important enough to warrant notification. They are of short duration, but the condition that they describe might affect the completion of the task or the quality of the output. When a warning message appears, the active job might be canceled. The message appears on the device control panel display for five seconds.

The following messages are generic warning messages that might appear on the device control panel display:

- **Device error**

  [enter] to cont.
- **Device is busy**

  Try again later

- **Engine comm.**

  error
- **Memory is low**

  Try again later
- **Page too complex**

  [enter] to cont.
- **Settings cleared**

If a warning message is related to a printing task and the auto continue setting is on, then the message appears for 10 seconds. If you do not press MENU/ENTER or CANCEL, the device continues processing the print job. If the auto continue setting is off, then the print-related warning message appears until you either press MENU/ENTER to proceed, or press CANCEL to cancel the job.

Note

The auto continue setting is available in the printer driver and the HP toolbox. To find out whether the auto continue setting is turned on, print a configuration page. See Printing a configuration page for more information.

No copy came out

Is media loaded in the input tray?

Load media in the device. See Loading originals to copy for more information.

Is the original loaded correctly?

Make sure that the original is loaded correctly in the automatic document feeder (ADF) input tray. The original should be loaded top down in the ADF input tray, with the side to be copied facing down. Insert the original into the ADF until it stops. See Loading originals to copy for more information.

Is the ADF media lever set correctly?

Make sure the automatic document feeder (ADF) media lever is in the correct position for the media you are using. Slide it to the single-sheet setting (to the right) when you are printing on thick media. Slide it to the multiple-sheet setting (to the left) when you are printing on regular media. For more information, see Loading originals to copy.

Copies are blank, or images are missing or faded

Has the sealing tape been removed from the print cartridge?

The sealing tape might not have been removed from the print cartridge. Remove the print cartridge from the device, pull out the sealing tape, and reinstall the print cartridge. See the start guide for information about installing a print cartridge.

Is the print cartridge low on toner?

The print cartridge is used for making copies. If the print cartridge is low on toner, the copies will be faded.

Is the original of poor quality?

The accuracy of the copy depends on the quality and size of the original. If your original is too light, the copy might not be able to compensate, even if you adjust the contrast.

Does the original have a colored background?

Colored backgrounds might cause images in the foreground to blend into the background, or the background might appear in a different shade.

Copy quality is unacceptable

This section provides information about the following topics:

- Preventing problems
- Identifying and correcting copy defects

Preventing problems

The following are a few simple steps you can take to improve copy quality:

- Use quality originals.
- Load the media correctly. If the media is loaded incorrectly, it might skew, causing unclear images and problems with the OCR program. See Loading originals to copy for instructions.
- If your device frequently feeds more than one page at a time, the separation pad might need to be replaced. Contact HP. See the support flyer that came with your device for information about contacting HP.
- Use or make a carrier sheet to protect your originals.

Note Recurring feed problems indicate the copier/separation pad is worn. See Ordering HP parts and accessories to order a new separation pad.

Media jams occur in the automatic document feeder (ADF)

Occasionally, media becomes jammed during a copy, scan, or fax job.

You are notified of a media jam by a software error message and the **Doc feeder jam Clear, Reload** message that appears on the device control panel display.

- The ADF input tray is loaded incorrectly or is too full. See Loading originals to copy for more information.
- The media does not meet HP specifications. See Selecting media for the automatic document feeder (ADF) for more information.

Typical automatic document feeder (ADF) jam locations

- Input tray areas: If the page is sticking out of the input tray, try to remove it gently from the input tray without tearing the page. If you feel resistance, see To clear a media jam from the automatic document feeder (ADF) for instructions.



- Output paths: If the page is sticking out of the output bin, try to remove it gently without tearing the page. If you feel resistance, see To clear a media jam from the automatic document feeder (ADF) for instructions.



- Intermediate location: If the page is sticking out of both the input tray and into the output area, see To clear a media jam from the automatic document feeder (ADF) for instructions.

Automatic document feeder (ADF) media lever

If you are using thick media, slide the media lever to the single-sheet setting (to the right). Load a single sheet of media into the ADF.

When you have finished, copying, scanning, or faxing, slide the ADF media lever back to the multiple-sheet setting (to the left).

To clear a media jam from the automatic document feeder (ADF)

1. Using both hands, pull the device control panel door toward you.



2. Remove any jammed media.



Note Use only your hands to remove jammed media. Using other objects can damage internal parts.

3. Make sure that all of the pieces of media are removed, and then close the device control panel door.



Copy defects are apparent

Vertical white or faded stripes



- The media might not meet Hewlett-Packard media specifications (for example, the media is too moist or too rough). See Device media specifications for more information.
- The toner might be low. See HP LaserJet print cartridges for instructions.

Blank pages

- The original might have been loaded upside down. In the automatic document feeder (ADF), load the original with the narrow side forward and the side to be scanned facing down. See Loading originals to scan for instructions.
- The media might not meet Hewlett-Packard media specifications (for example, the media is too moist or too rough). See Device media specifications for more information.
- The toner might be out. See the start guide for information about installing a print cartridge.
- The tape might not have been removed from the print cartridge. See the start guide for instructions.

Wrong original was copied

- Make sure that the automatic document feeder (ADF) is empty.

Too light or dark

- Try adjusting the settings.
- Make sure that the copy-quality settings are correct. See Adjusting the copy quality for more information.

Unwanted lines



- Make sure that the priority input slot is in place.
- Try cleaning the scanner glass. See Cleaning the outside of the device for instructions.
- The photosensitive drum inside the print cartridge might be scratched. Install a new HP print cartridge. See the start guide for instructions.

Black dots or streaks

- Ink, glue, correction fluid, or another unwanted substance might be on the automatic document feeder (ADF). Try cleaning the device. See Cleaning the outside of the device for instructions.

Unclear text

- Try adjusting the settings.
- Make sure that the copy-quality settings are correct. See Adjusting the copy quality for more information.
- See the device software Help for more information about changing the settings.

Reduced size

- The software settings might be set to reduce the scanned image.
- See the device software Help for more information about changing the settings.

Scanned image is of poor quality

Is the original a second-generation photo or picture?

Reprinted photographs, such as those in newspapers or magazines, are printed by using tiny dots of ink that make an interpretation of the original photograph, which dramatically decreases the quality. Often, the ink dots form unwanted patterns that can be detected when the image is scanned, printed, or appears onscreen. If the following suggestions do not solve your problem, you might need to use a better-quality version of the original.

- To eliminate the patterns, try reducing the size of the image after scanning.
- Print the scanned image to see if the quality is better.
- Make sure that your resolution and color settings are correct for the type of scan job that you are performing. See Scanner resolution and color for more information.

Is the image quality better when the document is printed?

The image that appears on the screen is not always an accurate representation of the quality of the scan.

- Try adjusting your computer monitor settings to use more colors (or levels of gray). Typically, you make this adjustment by opening **Display** in Windows Control Panel.
- Try adjusting the resolution and color settings in the scanner software. See Scanner resolution and color for more information.

Is the image skewed (crooked)?

The original might have been loaded incorrectly. Be sure to use the media guides when you load the originals into the automatic document feeder (ADF). See Loading originals to scan for more information.

Does the scanned image show blotting, lines, vertical white stripes, or any other defect?

If the scanner is dirty, the image that it produces does not have optimum clarity. See Cleaning the outside of the device for instructions.

Do graphics look different from the original?

The graphics settings might not be suitable for the type of scan job that you are performing. Try changing the graphics settings. See Scanner resolution and color for more information.

Part of the image did not scan

Was the original loaded correctly?

Make sure that you loaded the original correctly. See Loading originals to scan for instructions.

Does the original have a colored background?

Colored backgrounds can cause images in the foreground to blend into the background. Try adjusting the settings before you scan the original or enhancing the image after you scan the original. See Scanner resolution and color for more information.

Are text or images on the back of a two-sided original appearing in the scan?

Two-sided originals can "bleed" text or images from the back side to the scan if the originals are printed on media that is too thin or too transparent.

Is the original longer than 381 mm (15 inches)?

The maximum scannable length is 381 mm (15 inches) when you use the automatic document feeder (ADF). If the page exceeds the maximum length, the scanner stops. (Copies can be longer.)

CAUTION Do not try to pull the original from the ADF; you might damage the scanner or your original. See Media jams occur in the automatic document feeder (ADF) for instructions.

Is the original too small?

The minimum size that the automatic document feeder (ADF) supports is 51 by 89 mm (2 by 3.5 inches). The original might be jammed. See Media jams occur in the automatic document feeder (ADF) for instructions.

Is the media size correct?

In Scan settings, make sure that the input media size is large enough for the document that you are scanning. See Scanner resolution and color for more information.

The scan takes too long

Is your resolution or color level set too high?

If you set the resolution and color level too high, the scan job takes longer and results in larger files. To obtain good results when scanning or copying, it is important that you use the correct resolution and color level settings for your job. See Scanner resolution and color for more information.

Is your software set to scan in color?

The system default is color, which takes longer to scan even when scanning a monochrome original. If you acquire an image through TWAIN or WIA, you can change the settings so that the original scans in grayscale or black-and-white. See the device software Help for details.

Did you send a print job or copy job before you tried to scan?

If you sent a print job or copy job before you tried to scan, the scan will start if the scanner is not busy. However, the printer and scanner share memory, which means that the scan might be slower.

Is your computer set for bidirectional communication?

See the documentation that came with your computer to change the basic input/ouput settings (BIOS). The recommended bidirectional setting for the parallel port is ECP. The USB connection is always bidirectional.

Error messages appear

If one of the following messages appears on the screen, use this information to remedy the problem.

Common scanning error messages

This section describes common scanning error messages, and how to remedy them. The most common scanning error messages include the following:

- **Unable to activate TWAIN source**
- **An error occurred while acquiring the image**
- **Scanner initiation failed**
- **Error communicating with scanner**

Make sure that you have connected the USB Device Cable (A/B) or IEEE 1284-B-compliant parallel cable to the correct port on the back of your computer. If you have another port, try attaching the cable to the other port. Make sure that you have an EPP-(bidirectional) or ECP-compliant parallel port on your computer. An EPP parallel port is the minimum requirement; use of an ECP parallel port is strongly recommended. See the documentation that came with your computer for more information about your port.

Some devices might not share the parallel port with the device. If you have an external hard drive, or you have a network switchbox connected to the same USB or parallel port as the device, the other device might be interfering. To connect and use the device, you must disconnect the other device or you must use two ports on the computer. You might need to add another parallel interface card. Hewlett-Packard strongly recommends that you use an ECP parallel interface card. See the documentation that came with your computer for more information about installing an additional parallel interface card or resolving device conflicts.

Verify that the correct TWAIN source is selected. In the software, check the TWAIN source by selecting **Select Scanner** from the **File** menu.

Scan quality is unacceptable

This section provides information about improving scan quality by preventing or correcting problems.

Preventing problems

The following are a few simple steps you can take to improve copy and scan quality:

- Use high-quality originals.
- Load the media correctly. If the media is loaded incorrectly, it might skew, which causes unclear images. See Loading originals to scan for instructions.
- Adjust the software settings according to how you plan to use the scanned page. See Scanner resolution and color for more information.
- Recurring feed problems indicate that the separation pad is worn. See Ordering HP parts and accessories to order a new separation pad.
- Use or make a carrier sheet to protect your originals.

Blank pages

- The original might have been loaded upside down. In the automatic document feeder (ADF), put the top end of the stack of originals into the ADF, with the media stack face-down and the first page to be scanned on the bottom of the stack. See Loading originals to scan for instructions.

Too light or dark

- Try adjusting the settings.

  Make sure you have the correct resolution and color settings. See Scanner resolution and color for more information.

Unwanted lines

- Ink, glue, correction fluid, or an unwanted substance might be on the scanner. Try cleaning the scanner surface. See Cleaning the outside of the device for instructions.

Black dots or streaks

- Ink, glue, correction fluid, or an unwanted substance might be on the scanner surface. Try cleaning the scanner surface. See Cleaning the outside of the device for instructions.

Unclear text

- Try adjusting the settings.

  Make sure you have the correct resolution and color settings. See Scanner resolution and color for more information.

A Specifications

See these sections for specifications information about the following:

- HP LaserJet 3015 all-in-one
- HP LaserJet 3015 all-in-one battery

Physical specifications

Product	Height	Depth	Width	Weight
HP LaserJet 3015 all-in-one	445 mm (17.7 in)	470 mm (18.5 in)	426 mm (16.8 in)	9.1 kg (20 lbs)

Environmental specifications

Category	Specification
Operating environment (unit plugged into an AC outlet)	• Temperature: 15° to 32.5° C (59° to 90.5° F) • Humidity: 10 percent to 80 percent relative humidity (no condensation)
Storage environment (unit not plugged into an AC outlet)	• Temperature: -20° to 40° C (-4° to 104° F) • Humidity: Less than 95 percent relative humidity (with no condensation)

Electrical specifications[1]

Item	110-volt models	220-volt models
Power supply	110[2] to 127 V (+/- 10 %) 50 to 60 Hz (+/- 2 Hz)	220 to 240 V (+/- 10 %) 50 to 60 Hz (+/- 2 Hz)
Power consumption (typical)		
During printing	300 W (average)	300 W (average)
During standby	14 W (average)	14 W (average)
Power Save mode	14 W (average)	14 W (average)
Off mode	0 W (average)	0 W (average)
Heat output		
During printing	BTU/hr	BTU/hr

Item	110-volt models	220-volt models
Minimum recommended circuit capacity	4.5 A	2.3 A

[1]The values are subject to change. See http://www.hp.com/support/lj3015 for the most current information.
[2]Note: The power sources are not interchangeable.

Acoustic emissions[1]

Activity level	Operator (<1m)	Bystander (1m)	Sound power
Active	L_{pAm}56 dB (A)	L_{pAm}48 dB (A)	L_{WAd}6.1 Bels (A)
Idle	L_{pAm}N/A dB (A) (inaudible)	L_{pAm}N/A dB (A) (inaudible)	L_{WAd}N/A Bels (A) (inaudible)

[1]The values are subject to change. See http://www.hp.com/support/lj3015 for the most current information. During other operations, acoustic emissions can vary.

HP LaserJet 3015 all-in-one

- HP LaserJet 3015 all-in-one specifications
- Regulatory Information

HP LaserJet 3015 all-in-one specifications

Printer capacities and ratings	
Print speed	• 15 pages per minute (ppm) for letter size paper and 14 ppm for A4-size paper • First page out in less than 10 seconds
Media input tray capacity	150 sheets of regular-weight 60 g/m^2 (16 lb) paper or up to 30 envelopes
Priority input slot capacity	10 sheets of regular-weight 75 g/m^2 (20 lb) paper or 1 envelope
Output bin capacity	Up to 125 sheets of regular-weight 16 lb (60 g/m^2) paper
Minimum paper size	76 by 127 mm (3 by 5 inches)
Maximum paper size	216 by 356 mm (8.5 by 14 inches). The output bin holds one sheet of legal-size media (215 by 356 mm (8.5 by 14 inches)). Subsequent sheets of legal-size media slide off of the output bin.
Media weight	Output bin: 60 to 105 g/m^2 (16 to 28 lb)
Base memory	8 MB of ROM/Flash and 32 MB of RAM (9 MB for the device and 23 MB available to the user)
Print resolution	1200 dpi effective output quality (600x600x2 dpi, using HP Resolution Enhancement Technology [REt]).
Duty cycle	• 7,000 single-sided pages per month (maximum) • 800 single-sided pages per month (average)
PCL (Printer Control Language)	Level 5e and 6
PostScript (PS)	Emulates Adobe PostScript® Level 2
Copier capacities and ratings	
Copy speed	Up to 15 ppm
Multiple copies	Up to 99 per job
Copy reduction or enlargement	25 percent to 400 percent
Acoustic emissions (per ISO 9296) while copying	6.3 Bel sound power level
Scanner capacities and ratings	

Margins for scanned items	3.05 mm (0.12 inch) right and left 4.06 mm (0.16 inch) top and bottom
Scanner Duty Cycle	2,000 single-sided items per month
Scan resolution	600 dpi color
Automatic document feeder (ADF) input tray specifications	
Input capacity	Up to 30 sheets of flat 60 to 75 g/m^2 (16 to 20 lb) media
Media weight	60 to 105 g/m^2 (16 to 28 lb)
Media size	74 by 105 mm (2.9 by 4.1 inches) to 216 mm by 356 mm (8.5 by 14 inches). The ADF output bin holds one sheet of legal-size media (215 by 356 mm (8.5 by 14 inches)). Subsequent sheets of legal-size media slide off of the ADF output bin.
Speed	Up to 12 ppm for letter-size or A4-size media
Duty cycle	1,000 pages per month
Port availability	
USB	Compatible with USB 2.0 specification
Parallel	• IEEE 1284-B level 2 device with an IEEE 1284-B receptacle • Set the host computer to ECP (enhanced capabilities mode)
Fax capabilities and ratings	
Fax transmission speed	3 seconds per page (ITU-T Test Image #1)
Right/left margins for printed pages	6.3 mm (0.25 inch)
Top/bottom margins for printed pages	5.08 mm (0.2 inch)
Fax compatibility	ITU Group 3; ECM
Fax coding schemes	MH, MR, and MMR
Modem speed	Up to 33,600 bits per second (bps)
Speed dialing	Yes
Distinctive ring detect	Yes
Fax resolution (standard)	203 by 98 dpi
Fax resolution (fine)	203 by 196 dpi
Fax resolution (superfine)	300 by 300 dpi (no halftone)
Fax resolution (photo)	300 by 300 dpi (halftone enabled)
Fax page storage	Up to 110 Slerexe pages

HP LaserJet 3015 all-in-one battery

Battery material	Polycarbon Monoflouride Lithium
Battery type	Button or coin cell battery
Quantity per device	1
Weight	Approximately 1 gram
Lithium type	Solid
Battery manufacturers	Rayovac of Madison, Wisconsin, USA; and Panasonic of Secaucus, New Jersey, USA.

B Regulatory Information

See these sections for regulatory information:

- FCC regulations
- Telephone consumer protection act (United States)
- IC CS-03 requirements
- Regulatory information for the European Union countries/regions
- Safety statements
- Declaration of Conformity
- Environmental product stewardship program
- Material safety data sheets

FCC regulations

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy. If not installed and used in accordance with the instructions, it may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase separation between equipment and receiver.
- Connect equipment to an outlet on a circuit different from that to which the receiver is located.
- Consult your dealer or an experienced radio/TV technician.

Note Any changes or modifications to the printer that are not expressly approved by HP could void the user's authority to operate this equipment.

Note Use of a shielded interface cable is required to comply with the Class B limits of Part 15 of FCC rules.

FCC Part 68 Requirements (United States)

This equipment complies with FCC rules, Part 68. On the back of this equipment is a label that contains, among other information, the FCC registration number and ringer equivalence number (REN) for this equipment. If requested, this information must be provided to the telephone company. The REN is used to determine the quantity of devices which may be connected to the telephone line. Excessive RENs on the telephone line may result in the devices not ringing in response to an incoming call. In most, but not all, areas, the sum of the RENs should not exceed five (5.0). To be certain of the number of devices that may be connected to the line, as determined by the total RENs, contact the telephone company to determine the maximum REN for the calling area.

This equipment uses the following USOC jacks: RJ11C.

An FCC-compliant telephone cord and modular plug is provided with this equipment. This equipment is designed to be connected to the telephone network or premises wiring using a compatible modular jack which is Part 68 compliant. This equipment cannot be used on telephone company-provided coin service. Connection to Party Line Service is subject to state tariffs. If this equipment causes harm to the telephone network, the telephone company will notify you in advance that temporary discontinuance of service may be required. If advance notice isn't practical, the telephone company will notify the customer as soon as possible. Also, you will be advised of your right to file a complaint with the FCC if you believe it is necessary. The telephone company may make changes in its facilities, equipment, operations, or procedures that could affect the operation of the equipment. If this happens, the telephone company will provide advance notice in order for you to make the necessary modifications in order to maintain uninterrupted service. If trouble is experienced with this equipment, please see the numbers in the front of this manual for repair and (or) warranty information. If the trouble is causing harm to the telephone network, the telephone company may request you remove the equipment from the network until the problem is resolved. The following repairs can be done by the customer: Replace any original equipment that came with the product. This includes the print cartridge, the supports for trays and bins, the power cord, and the telephone cord. It is recommended that the customer install an AC surge arrestor in the AC outlet to which this device is connected. This is to avoid damage to the equipment caused by local lightning strikes and other electrical surges.

Telephone consumer protection act (United States)

The Telephone Consumer Protection Act of 1991 makes it unlawful for any person to use a computer or other electronic device, including fax machines, to send any message unless such message clearly contains, in a margin at the top or bottom of each transmitted page or on the first page of the transmission, the date and time it is sent and an identification of the business, other entity, or individual sending the message and the telephone number of the sending machine or such business, other entity, or individual. (The telephone number provided cannot be a 900 number or any other number for which charges exceed local or long-distance transmission charges.) In order to program this information into your facsimile, please see the fax guide.

IC CS-03 requirements

NOTICE: The Industry Canada label identifies certified equipment. This certification means the equipment meets certain telecommunications network protective, operational, and safety requirements as prescribed in the appropriate Terminal Equipment Technical Requirement document(s). The Department does not guarantee the equipment will operate to the user's satisfaction. Before installing this equipment, users should ensure that it is permissible for the equipment to be connected to the facilities of the local telecommunications company. The equipment must also be installed using an acceptable method of connection. The customer should be aware that compliance with the above conditions may not prevent degradation of service in some situations. Repairs to certified equipment should be coordinated by a representative designated by the supplier. Any repairs or alterations made by the user to this equipment, or equipment malfunctions, may give the telecommunications company cause to request the user to disconnect the equipment. Users should ensure for their own protection that the electrical ground connections of the power utility, telephone lines, and internal metallic water pipe system, if present, are connected together. This precaution can be particularly important in rural areas.

CAUTION Users should not attempt to make such connections themselves, but should contact the appropriate electric inspection authority, or electrician, as appropriate. The Ringer Equivalence Number (REN) of this device is 0.7.

Notice: The Ringer Equivalence Number (REN) assigned to each terminal device provides an indication of the maximum number of terminals allowed to be connected to a telephone interface. The termination on an interface may consist of any combination of devices subject only to the requirement that the sum of the Ringer Equivalence Number of all the devices does not exceed five (5.0). The standard connecting arrangement code (telephone jack type) for equipment with direct connections to the telephone network is CA11A.

Regulatory information for the European Union countries/regions

This equipment has been designed to work in all of the countries/regions of the European Economic Area (Public Switched Telephone Networks) only. Network compatibility is dependent on internal software settings. Contact your equipment supplier if it is necessary to use the equipment on a different telephone network. For further product support, contact Hewlett-Packard at the phone numbers provided in the support flyer that came with the product.

Safety statements

Laser safety statement

The Center for Devices and Radiological Health (CDRH) of the U.S. Food and Drug Administration has implemented regulations for laser products manufactured since August 1, 1976. Compliance is mandatory for products marketed in the United States. This printer is certified as a “Class 1” laser product under the U.S. Department of Health and Human Services (DHHS) Radiation Performance Standard according to the Radiation Control for Health and Safety Act of 1968. Since radiation emitted inside this printer is completely confined within protective housings and external covers, the laser beam cannot escape during any phase of normal user operation.

WARNING! Using controls, making adjustments, or performing procedures other than those specified in this manual can result in exposure to hazardous radiation.

Canada DOC regulations

This equipment complies with Canadian EMC Class B requirements.

Conforme á la classe B des normes canadiennes de compatibilité électromagnétiques. << CEM>>.

Laser statement for Finland

LASERTURVALLISUUS

LUOKAN 1 LASERLAITE

KLASS 1 LASER APPARAT

HP LaserJet 3015 all-in-one-laserkirjoitin on käyttäjän kannalta turvallinen luokan 1 laserlaite. Normaalissa käytössä kirjoittimen suojakotelointi estää lasersäteen pääsyn laitteen ulkopuolelle.

Laitteen turvallisuusluokka on määritetty standardin EN 60825-1:1994 + A11:1996 + A2:2001 mukaisesti.

VAROITUS!

Laitteen käyttäminen muulla kuin käyttöohjeessa mainitulla tavalla saattaa altistaa käyttäjän turvallisuusluokan 1 ylittävälle näkymättömälle lasersäteilylle.

VARNING!

Om apparaten används på annat sätt än i bruksanvisning specificerats, kan användaren utsättas för osynlig laserstrålning, som överskrider gränsen för laserklass 1.

HUOLTO

HP LaserJet 3015 all-in-one-kirjoittimen sisällä ei ole käyttäjän huollettavissa olevia kohteita. Laitteen saa avata ja huoltaa ainoastaan sen huoltamiseen koulutettu henkilö. Tällaiseksi huoltotoimenpiteeksi ei katsota väriainekasetin vaihtamista, paperiradan puhdistusta tai muita käyttäjän käsikirjassa lueteltuja, käyttäjän tehtäväksi tarkoitettuja ylläpitotoimia, jotka voidaan suorittaa ilman erikoistyökaluja.

VARO!

Mikäli kirjoittimen suojakotelo avataan, olet alttiina näkymättömälle lasersäteilylle laitteen ollessa toiminnassa. Älä katso säteeseen.

VARNING!

Om laserprinterns skyddshölje öppnas då apparaten är i funktion, utsättas användaren för osynlig laserstrålning. Betrakta ej strålen.

Tiedot laitteessa käytettävän laserdiodin säteilyominaisuuksista:

Aallonpituus 770-795 nm

Teho 5 mW

Luokan 3B laser

Korean EMI statement

사용자 안내문 (B급 기기)

이 기기는 비업무용으로 전자파장해 검정을 받은 기기로서, 주거지역에서는 물론 모든지역에서 사용할 수 있읍니다.

Australia

This equipment complies with Australian EMC requirements.

Declaration of Conformity

Declaration of Conformity
according to ISO/IEC Guide 22 and EN 45014

Manufacturer's Name:	Hewlett-Packard Company
Manufacturer's Address:	11311 Chinden Boulevard Boise, Idaho 83714-1021, USA

declares that the product

Product Name:	HP LaserJet 3015 all-in-one
Product Number:	Q2669A (Regulatory Model[3]: BOISB-0307-00
Product Options:	All

conforms to the following Product Specifications:

Safety:	IEC 60950:1999 / EN60950:2000 IEC 60825-1:1993 + A1:1996 + A2:2001 / EN 60825-1:1994 + A11:1996 + A2:2001 (Class 1 Laser/LED Product) GB4943-1995
EMC:	CISPR 22:1998 / EN 55022:1998 - Class B[1] EN 61000-3-2:1995 / A14:2000 EN 61000-3-3:1995 EN 55024:1998 FCC Title 47 CFR, Part 15 Class B[2] / ICES-003, Issue 3 GB9254-1998 Telecom: TBR-21:1998; EG 201 121:1998

Supplementary Information:

The product herewith complies with the requirements of the EMC Directive 89/336/EEC, the Low Voltage Directive 73/23/EEC, the R&TTE Directive 1999/5/EC (Annex II), and carries the CE-Marking accordingly

[1]The product was tested in a typical configuration with Hewlett-Packard Personal Computer Systems

[2]This Device complies with Part 15 of the FCC Rules. Operation is subject to the following two Conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation

[3]For regulatory purposes, this product is assigned a Regulatory model number. This number should not be confused with the marketing name (HP LaserJet 3015) or the product number (Q2669A).

Boise, Idaho 83713, USA

November 1, 2003

For Regulatory Topics Only:

Australia Contact	Product Regulations Manager, Hewlett-Packard Australia, Ltd. 31-41 Joseph Street Blackburn, Victoria 3130, Australia
European Contact	Your Local Hewlett-Packard Sales and Service Office or Hewlett-Packard Gmbh, Department HQ-TRE / Standards Europe Herrenberger Strasse 140 Böblingen, D-71034, (+49-7031-14-3143)
USA Contact	Product Relations Manager, Hewlett-Packard Company PO Box 15, Mail Stop 160 Boise, ID 83707-0015, USA (208-396-6000)

Environmental product stewardship program

Protecting the environment

Hewlett-Packard Company is committed to providing quality products in an environmentally sound manner. This product has been designed with several attributes to minimize impacts on our environment.

Ozone production

This product generates no appreciable ozone gas (O3).

Energy consumption

Energy usage drops significantly while in Power Save mode, which saves natural resources and saves money without affecting the high performance of this product. This product qualifies for ENERGY STAR® (version 1.0), which is a voluntary program to encourage the development of energy-efficient office products.

ENERGY STAR® is a U.S. registered service mark of the U.S. Environmental Protection Agency. As an ENERGY STAR® Partner, Hewlett-Packard Company has determined this product meets ENERGY STAR® Guidelines (version 1.0) for energy efficiency. For more information, see http://www.energystar.gov.

Toner consumption

EconoMode/Toner Miser uses significantly less toner, which might extend the life of the print cartridge.

Paper use

This product's manual duplex feature (two-sided printing, see Printing on both sides of the media (manual duplexing)), and printing multiple pages on one page can reduce paper usage and the resulting demands on natural resources.

Plastics

Plastic parts over 25 grams are marked according to international standards that enhance the ability to identify plastics for recycling purposes at the end of the product's life.

HP LaserJet printing supplies

In many countries/regions, this product's printing supplies (for example, print cartridge, drum, fuser) can be returned to HP through the HP Printing Supplies Returns and Recycling Program. An easy to use and free takeback program is available in over 48 countries/regions. Multi-lingual program information and instructions are included in every new HP LaserJet print cartridge and consumables package.

HP printing supplies returns and recycling program information

Since 1990, the HP Printing Supplies Returns and Recycling Program has collected millions of used LaserJet print cartridges that otherwise may have been discarded in the world's landfills. The HP LaserJet print cartridges and supplies are collected and bulk shipped to our resource and recovery partners who disassemble the cartridge. After a thorough quality inspection, selected parts are reclaimed for use in new cartridges. Remaining materials are separated and converted into raw materials for use by other industries to make a variety of useful products.

U.S. returns

For a more environmentally responsible return of used cartridges and supplies, HP encourages the use of bulk returns. Simply bundle two or more cartridges together and use the single, pre-paid, pre-addressed UPS label that is supplied in the package. For more information in the U.S., call (1) (800) (340-2445) or visit the HP LaserJet Supplies website at http://www.hp.com/recycle.

Non-U.S. returns

Non-U.S. customers should call the local HP Sales and Service Office or visit the http://www.hp.com/recycle web site for further information regarding availability of the HP Supplies Returns and Recycling Program.

Paper

This product is capable of using recycled papers when the paper meets the guidelines outlined in the Print Media Guide. See Device media specifications for more information. This product is suitable for the use of recycled paper according to DIN 19309.

Material restrictions

This HP product contains mercury in the fluorescent lamp or scanner that may require special handling at end-of-life.

This HP product contains lead in solder.

This HP product contains a battery that might require special handling at end of life.

Type:	Lithium Carbon Monofluoride (solid button cell)

Weight:	approx. 1 gram
Location:	on formatter PC board (one battery per product)
User Removable:	No

For recycling information, you can contact http://www.hp.com/go/recycle or contact your local authorities or the Electronics Industries Alliance: http://www.eiae.org.

Nederlands

Toepassing: De batterij wordt gebruikt als reserve-energiebron voor de tijdklok (die wordt gebruikt voor het faxgedeelte van het apparaat).

Locatie van de batterij: De batterij wordt bij de fabricage/distributie van het product op de formatter gesoldeerd.

Voorschriften:

- · Richtlijn van de Europese Unie met betrekking tot batterijen: Deze batterij komt niet in aanmerking voor de richtlijnen.
- · Bijzondere bepaling A45 voor UN-standaard: Deze batterij is een niet-gevaarlijk artikel.

Levensduur: De batterij is ontworpen om minstens even lang mee te gaan als het product.

Batterijfabrikanten: Rayovac, Madison, WI, USA; and Panasonic, Secaucus, NJ, USA.

Het ontwerp en de specificaties kunnen zonder kennisgeving worden gewijzigd.

For more information

On HP's environmental programs, including:

- Product environmental profile sheet for this and many related HP products
- HP's commitment to the environment
- HP's environmental management system
- HP's end-of-life product return and recycling program
- Material Safety Data Sheets

See: http://www.hp.com/go/environment or http://www.hp.com/hpinfo/community/environment/.

Material safety data sheets

Material Safety Data Sheets (MSDS) can be obtained by contacting the HP LaserJet Supplies web site at http://www.hp.com/hpinfo/community/environment/productinfo/safety.htm.

C HP limited warranty statement

HP LaserJet 3015 all-in-one ONE-YEAR LIMITED WARRANTY

HP PRODUCT	DURATION OF LIMITED WARRANTY
HP LaserJet 3015 all-in-one	One year

HP warrants to you, the end-user customer, that HP hardware, accessories, and supplies will be free from defects in materials and workmanship after the date of purchase, for the period specified above. If HP receives notice of such defects during the warranty period, HP will, at its option, either repair or replace products which prove to be defective. Replacement products may be either new or equivalent in performance to new.

HP warrants to you that HP software will not fail to execute its programming instructions after the date of purchase, for the period specified above, due to defects in material and workmanship when properly installed and used. If HP receives notice of such defects during the warranty period, HP will replace software which does not execute its programming instructions due to such defects.

HP does not warrant that the operation of HP products will be uninterrupted or error free. If HP is unable, within a reasonable time, to repair or replace any product to a condition as warranted, you will be entitled to a refund of the purchase price upon prompt return of the product.

HP products may contain remanufactured parts equivalent to new in performance or may have been subject to incidental use.

Warranty does not apply to defects resulting from (a) improper or inadequate maintenance or calibration, (b) software, interfacing, parts, or supplies not supplied by HP, (c) unauthorized modification or misuse, (d) operation outside of the published environmental specifications for the product, or (e) improper site preparation or maintenance. TO THE EXTENT ALLOWED BY LOCAL LAW, THE ABOVE WARRANTIES ARE EXCLUSIVE AND NO OTHER WARRANTY OR CONDITION, WHETHER WRITTEN OR ORAL, IS EXPRESSED OR IMPLIED AND HP SPECIFICALLY DISCLAIMS ANY IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY, SATISFACTORY QUALITY, AND FITNESS FOR A PARTICULAR PURPOSE. Some countries/regions, states, or provinces do not allow limitations on the duration of an implied warranty, so the above limitation or exclusion might not apply to you. This warranty gives you specific legal rights and you might also have other rights that vary from country/region to country/region, state to state, or province to province.

HP’s limited warranty is valid in any country/region or locality where HP has a support presence for this product and where HP has marketed this product. The level of warranty service you receive may vary according to local standards. HP will not alter form, fit, or function of the product to make it operate in a country/region for which it was never intended to function for legal or regulatory reasons.

TO THE EXTENT ALLOWED BY LOCAL LAW, THE REMEDIES IN THIS WARRANTY STATEMENT ARE YOUR SOLE AND EXCLUSIVE REMEDIES. EXCEPT AS INDICATED ABOVE, IN NO EVENT WILL HP OR ITS SUPPLIERS BE LIABLE FOR LOSS OF DATA OR FOR DIRECT, SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFIT OR DATA), OR OTHER DAMAGE, WHETHER BASED IN CONTRACT, TORT, OR OTHERWISE. Some countries/regions, states, or provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

THE WARRANTY TERMS CONTAINED IN THIS STATEMENT, EXCEPT TO THE EXTENT LAWFULLY PERMITTED, DO NOT EXCLUDE, RESTRICT, OR MODIFY AND ARE IN ADDITION TO THE MANDATORY STATUTORY RIGHTS APPLICABLE TO THE SALE OF THIS PRODUCT TO YOU.

D HP parts and accessories

Use the following topics to find out about ordering parts and accessories for your device:

- Ordering HP parts and accessories
- HP LaserJet print cartridges

Ordering HP parts and accessories

HP parts and accessories chart

You can increase the device's capabilities with optional accessories and supplies. Use accessories and supplies designed specifically for your HP LaserJet 3015 all-in-one to ensure optimum performance.

Accessories

Product name	Description	Part number
Cables and interface accessories	2-meter IEEE–1284 parallel cable	C2950A
Cables and interface accessories	3-meter IEEE-1284 parallel cable	C2951A
Cables and interface accessories	2-meter USB Device Cable (A/B)	8121-0539
Print cartridge accessories	Toner collection cloth	5090-3379

Printing supplies

Product name	Description	Part number
HP Multipurpose paper	HP brand paper for a variety of uses (1 box of 10 reams, 500 sheets each).	HPM1120
HP LaserJet paper	Premium HP brand paper for use with HP LaserJet printers (1 box of 10 reams, 500 sheets each).	HPJ1124
HP LaserJet transparency film	HP brand transparency film for use with HP LaserJet monochrome printers.	92296U (A4)
HP LaserJet transparency film	HP brand transparency film for use with HP LaserJet monochrome printers.	92296T (letter)
Print cartridges	Replacement print cartridges for the HP LaserJet 3015 all-in-one. 2,000 page cartridge	C7115A

Supplementary documentation

Product name	Description	Part number
Guidelines for Paper and Other Print Media	A guide to using paper and other print media with HP LaserJet printers.	5963-7863

Replacement parts

Product name	Description	Part number
Paper pickup roller	Used to pick the media from the input tray and advance it through the device.	RF0-1008-000CN
Media input tray	Used to hold media for the device.	RG0-1121-000CN
Priority input slot	Used to feed special media or for printing a first page.	RG0-1122-000CN
Automatic document feeder (ADF) input tray	Used to feed documents into the scanner.	C9143-60102
Separation pad for the device	Used to keep multiple sheets from feeding through the device path.	RF0-1014-000CN
ADF pickup roller assembly	Used to pick the media from the ADF input tray and advance it through the ADF.	C7309-60016
ADF	If your ADF breaks, use this part number to order one.	C9143-60101

HP LaserJet print cartridges

This section contains information about using HP LaserJet print cartridges.

HP policy on non-HP print cartridges

Hewlett-Packard Company cannot recommend the use of non-HP print cartridges, either new, refilled, or remanufactured. Because they are not HP products, HP cannot influence their design or control their quality. Service or repair required as a result of using a non-HP print cartridge will not be covered under the printer warranty.

Note The warranty does not apply to defects resulting from software, interfacing, or parts not supplied by HP.

To install a print cartridge

To install a print cartridge, see the start guide.

Storing print cartridges

Do not remove the print cartridge from its package until you are ready to use it. Some HP LaserJet print cartridge packages are stamped with an alphanumeric date code. This code represents a 30-month period beyond the date of production in order to facilitate efficient inventory management processes between HP and its resellers. It does not serve as an indication of toner life (shelf-life) or relate in any way to warranty terms and conditions.

CAUTION To prevent damage to the print cartridge, do not expose it to light.

Print cartridge life expectancy

The life of the print cartridge depends on the amount of toner that your print jobs require. When printing text on letter/A4-size paper at 5 percent coverage, the print cartridge lasts an average of 2,000 pages. This assumes that you set the print density to 3 and turn EconoMode off (these are the default settings).

Recycling print cartridges

Since 1990, the HP Printing Supplies Returns and Recycling Program has collected millions of used LaserJet print cartridges that otherwise may have been discarded in the world's landfills. The HP LaserJet print cartridges and supplies are collected and bulk shipped to our resource and recovery partners who disassemble the cartridge. After a thorough quality inspection, selected parts are reclaimed for use in new cartridges. Remaining materials are separated and converted into raw materials for use by other industries to make a variety of useful products.

U.S. returns

For a more environmentally responsible return of used cartridges and supplies, HP encourages the use of bulk returns. Simply bundle two or more cartridges together and use the single, pre-paid, pre-addressed UPS label that is supplied in the package. For more information in the U.S., call (800) 340-2445, or visit the HP LaserJet Supplies website at http://www.hp.com/recycle.

Saving toner

To save toner, select the EconoMode option in your device properties settings. (For more information, see To use EconoMode (to save toner).) While in EconoMode (Save Toner), the device uses less toner on each page. Selecting this option extends the life of the print cartridge and reduces your cost per page, but it also reduces print quality. HP does not recommend the full-time use of EconoMode. See Print cartridge life expectancy for more information.

E Service and support

Use these topics to learn about obtaining device service and support.

- Obtaining hardware service
- Extended warranty
- Service information form

Obtaining hardware service

Note Warranty service and support options might vary depending on your country/region. For additional support information, visit http://www.hp.com.

To obtain hardware service

If your hardware should fail during the warranty period, HP offers the following support options:

- **HP repair services.** You can return the device to an HP repair center, depending on your location. You can also obtain telephone support by calling the appropriate telephone number listed on the support flyer that came with the device.
- **HP authorized service provider.** You can return the unit to a local authorized service dealer.

Returning the unit

When shipping equipment, HP recommends insuring it. Also, include a copy of your proof of purchase. Please also fill out the Service information form to ensure the most accurate repairs.

CAUTION Shipping damage resulting from inadequate packaging is the customer's responsibility. See the following repackaging guidelines.

Repackaging guidelines

- If possible, print a self-test page (see Printing a configuration page) before you turn off the unit, and send the self-test report with the unit.
- Remove and retain the print cartridge.

CAUTION Toner left in the device during shipping can damage the device.

- Remove the media input tray and repackage it using the original packaging materials, if possible. See To remove the media input tray for instructions.
- Include the completed copy of the service information form below. Note on the form which items were returned.
- Use the original shipping container and packaging materials, if possible.
- Include samples that illustrate the problems you are having, if applicable.
- Include five sheets of the paper or other media that are causing trouble in printing, scanning, faxing, or copying. Seal the paper or media in an airtight bag.

To remove the media input tray

Note

You might need to remove the media input tray to return the device. Use the following instructions to remove the media input tray without damaging the device.

1. Open the media input tray and remove any media.



2. Slide the media guides inward as far as they will go. Press and hold down the tabs inside the media input tray, and slide the media input tray out of the device.



Extended warranty

In most countries/regions, HP CarePack provides additional—beyond standard warranty—coverage for the HP product and all HP-supplied internal components. This hardware maintenance can uplift the standard warranty (i.e. from next-day to same-day service) and/or extend it up to five years. The HP CarePack can provide Express Exchange or onsite service. For more support information, contact the Customer Care Service and Support group; see the support flyer that came with your device for the appropriate phone numbers and information.

Service information form

Who is returning the equipment?		Date:
Person to contact:		Phone:
Alternate contact:		Phone:
Return shipping address:		Special shipping instructions:
What is being sent?	Model number:	Serial number:
Please attach any relevant printouts when returning equipment. **Do not** ship accessories that are not required to complete the repair (for example, media trays, manuals, and cleaning supplies).		
What needs to be done? 1. Describe the conditions of the failure (What was the failure? What were you doing when the failure occurred? What software were you running? Can you make the failure reoccur?).		
2. If the failure is intermittent, how much time elapses between failures?		
3. Is the unit connected to any of the following? (Please provide manufacturer and model numbers.)		
Personal Computer:	Modem:	Network:
4. Additional comments:		

Glossary

1284-B

The 1284 parallel port standard was developed by the Institute of Electrical and Electronics Engineers (IEEE). The term "1284-B" refers to a specific connector type on the end of the parallel cable that attaches to the peripheral (for example, a printer). A 1284-B connector is larger than a 1284-C connector, for example.

ADF

Automatic document feeder. The ADF is used to automatically feed originals into the device for copying, scanning, or faxing.

all-in-one

A designation given to HP devices that can perform several functions, such as printing, faxing, copying, and scanning.

browser

Short for Web browser, a software program that is used to locate and open Web pages.

collate

The process of printing a multiple-copy job in sets. When collate is selected, the device prints an entire set before printing additional copies. Otherwise, the device prints the specified number of copies of one page before printing the subsequent pages.

contrast

The difference between the dark and light areas of an image. The lower the number value, the more closely the shades resemble each other. The higher the number, the more the shades appear separate from each other.

DIMMs

Dual inline memory module, a small circuit board that holds memory. A single in-line memory module (SIMM) has a 32-bit path to the memory, whereas a DIMM has a 64-bit path.

dots per inch (dpi)

A measurement of resolution that is used for scanning and printing. Generally, more dots per inch result in a higher resolution, more visible detail in the image, and a larger file size.

dpi

See dots per inch (dpi).

e-mail (electronic mail)

An abbreviation for electronic mail. Software that can be used to electronically transmit items over a communications network.

EconoMode

EconoMode is a toner-saving feature on the device. EconoMode reduces the amount of toner on a printed page, so that the print cartridge lasts longer. The printed result is similar to printing a document in draft mode.

ECP

Extended capabilities port, a parallel-port standard for computers that supports bidirectional communication between the computer and attached devices (such as a printer).

file format

The way the contents of a file are structured by a program or group of programs.

grayscale

Shades of gray that represent light and dark portions of an image when color images are converted to grayscale; colors are represented by various shades of gray.

halftone

An image type that simulates grayscale by varying the number of dots. Highly colored areas consist of a large number of dots, while lighter areas consist of a smaller number of dots.

HP Director toolbar

Available for Macintosh only. A software screen that is used when working with documents. When the document is loaded into the automatic document feeder (ADF) and the computer is connected directly to the device, the HP Director appears on the computer screen to initiate faxing, copying, or scanning.

HP toolbox

The HP toolbox is a Web page that opens in a Web browser and provides access to the device management and troubleshooting tools, embedded Web server, and device documentation.

link

A connection to a program or device that can be used to send information from the device software to other programs, such as e-mail, electronic fax, and OCR links.

Optical Character Recognition (OCR) software

OCR software converts an electronic image of text, such as a scanned document, into a form that word processor, spreadsheet, and database programs can use.

parallel cable

See 1284-B.

printer driver

A printer driver is a program that software programs use to gain access to a device's features. A printer driver translates a software program's formatting commands (such as page breaks and font selection) into a printer language (such as PostScript or PCL), and then sends the print file to the device.

Readiris

An optical character recognition (OCR) program that was developed by I.R.I.S. and that is included with the device software.

resolution

The sharpness of an image, measured in dots per inch (dpi). The higher the dpi, the greater the resolution.

surge protector

A device that protects a power supply and communications lines from electrical surges.

TWAIN

An industry standard for scanners and software. By using a TWAIN-compliant scanner with a TWAIN-compliant program, a scan can be initiated from within the program.

URL

Uniform resource locator, the global address of documents and resources on the Internet. The first part of the address indicates what protocol to use, the second part specifies the IP address or the domain name where the resource is located.

USB (compatible with 2.0 specifications)

Universal serial bus (USB) is a standard that was developed by the USB Implementers Forum, Inc., to connect computers and peripherals. Unlike the parallel port, USB is designed to concurrently connect a single computer USB port to multiple peripherals.

watermarks

A watermark adds background text to a document that is being printed. For example, “Confidential” can be printed in the background text of a document to indicate that the document is confidential. A selection can be made from a set of predefined watermarks, and the font, size, angle, and style can be changed. The printer can place the watermark on the first page only or all pages.

WIA

Windows Imaging Architecture (WIA) is an imaging architecture that is available in Windows Me and Windows XP. A scan can be initiated from within these operating systems by using a WIA-compliant scanner.

Index

Symbols/Numerics
2-sided originals
  copying 54
2-sided printing 37
300 dpi print-quality setting 21
600 dpi print-quality setting 21

A
accessories and parts 132
acoustic emissions 112
acoustic emissions while copying 113
ADF
  clearing jams 102
  duty cycle 114
  input tray 4
  loading input tray 56
  media specifications 8
  ordering parts 133
  output bin 4
  selecting media 29
  specifications 29, 114
adjusting
  contrast default for copying 48
  contrast for current copy job 48
  copy quality 47
  default copy size 49
  device control panel key-press volume 16
  languages, device control panel display 14
  settings 9
  settings from the computer 20
  volume 14
alarm volume
  adjusting 15
alcohol, cleaning with 72
alert messages 97
Australia
  EMC statements 123

B
battery specifications 115
Best Quality (ProRes 1200) print-quality setting 21
black dots 105
blank pages 78, 104
booklets, printing 40
buttons on device control panel 5

C
cables
  interface, ordering 132
Canada DOC regulations 121
canceling
  copy jobs 46
  print jobs 19
  scan jobs 59
card stock
  media sizes and weights 7
  printing 36
  specifications 27
changing
  device control panel display language 14
  number of copies 53
  print quality settings 21
  settings from the computer 20
  settings, default 9, 20
  volume 14
characters
  dropouts 90
  misformed 93
  unclear 105
cleaning
  exterior 72
  glass 72
  printer media path 73
clearing jams
  ADF 102
  media 85
collating copies
  changing defaults 52
  description 52
color scanning 66
components 4
contrast
  setting default for copying 48
  setting for current copy job 48
copier capacities and ratings 113
copy contrast setting
  adjusting default 48
  adjusting for current copy job 48
copy quality
  adjusting 47
  defaults, adjusting 48
  improving and preventing problems 101
  See also image quality, troubleshooting, copy quality

copying
acoustic emissions 113
adjusting default copy size 49
canceling 46
changing number of copies 53
enlarging 49
multipage stack of 2-sided originals 54
reducing 49
reduction and enlargement capability 113
speed 113
starting a job 46
troubleshooting 99, 100, 101, 104
creases, troubleshooting 94
critical error messages 96
crooked printing 82
curled media 82
curling, troubleshooting 94
custom media
printing 36
Custom print-quality setting 21
customer support
form, service 141
hardware service 138

D
dark copying 105
darkness
setting default for copying 48
setting for current copy job 48
Declaration of Conformity 121, 124
default settings
adjusting 20
restoring 13
device control panel
components 5
key-press volume, adjusting 16
languages, changing 14
location 4
messages 96
printing configuration page 13
printing menu map 13
scanning from 60
device features 3
dimensions, device 111
documentation
ordering 133
draft-quality printing 21
drivers, printer, requirements for 20
dropouts, character 90
duplexing, manual 37
duty cycle
ADF 114
device 113
scanner 114

E
e-mail, scanning to 60
EconoMode 21
EconoMode (Save Toner) print-quality setting 21
electrical specifications
device 111
EMC statement for Australia 123
EMI statement for Korea 122
energy consumption 125
ENERGY STAR 125
enlarging
copies 49
envelopes
printing 30
specifications for 26
Environmental Product Stewardship Program 125
environmental specifications 111
equipment components 4
error messages
computer screen 81, 109
device control panel 96
European Union regulatory information 120
Express Exchange repair service 138
extended warranty 140

F
factory settings
restoring 13
Faster Printing (FastRes 1200) print-quality setting 21
FastRes 1200 print-quality setting 21
fax sounds
adjusting volume 15
faxing
margins 114
resolution 114
speed 114
FCC regulations 118
features 2, 3
feeding manually 18
feeding problems 82
Finland laser statement 122
folder, scanning to a 60
forms
printing 35
service information 141

G
glossary of terms 143
graphics
look different from original when scanned 106
poor quality 84
graphics, missing 83
gray backgrounds, troubleshooting 91

H
hardware components 4
hardware service 138
heat output 111
height, device 111

HP LaserJet 3015 all-in-one
package contents 2
HP LaserJet Fax 6
HP LaserJet Printer Family Print Media Guide 24
HP LaserJet Scan software, scanning with 61
HP limited warranty statement 129
HP repair services 138
HP SupportPack 140
HP toolbox 6
humidity
specifications 111

I
IC CS-03 requirements 120
image quality, troubleshooting
black dots 105, 110
blank copies 100
blank pages 78, 104, 110
characters, misformed 93
curl or wave 94
dropouts 90
faded images 100
faded print 89
graphics 106
gray backgrounds 91
improving and preventing problems 101
light or dark print 105
light print 89
lines 90, 110
loose toner 92
missing images 100
reduced size 105
repeating defects 92
skewed pages 93, 106
smears 91
specks 89
streaks 105, 110
unclear text 105
unwanted lines 105
vertical repetitive defects 92
vertical white or faded stripes 104
input tray, media
illustration 4
ordering 133
input tray, paper
capacity, main 113
capacity, priority 113
media specifications 7
installing
print cartridge 134
interface accessories, ordering 132

J
jams
ADF, typical locations 102
clearing 85
preventing 88

K
key-press volume
adjusting 16
Korean EMI statement 122

L
labels
media sizes and weights 7
printing 33
specifications for 25
language for device control panel display
changing 14
laser safety statement 121
length, device 111
letterhead, printing 35
life expectancy for print cartridges 134
light copying 105
light print 89
lightness
setting default for copying 48
setting for current copy job 48
limited one-year warranty 129
lines on copy
unwanted 105
loading
originals 44, 45, 56
loose toner, troubleshooting 92
LPT1, error printing to 81

M
manual duplexing 37
manual feed 18
margins
faxing 114
margins for scanned items 114
material restrictions 126
Material Safety Data Sheets (MSDS) 128
media
common problems 25
guidelines 25
optimizing print quality 23
size, maximum 113
size, minimum 113
sizes, default adjustments 14
specifications 7, 24
weight 113
media path, cleaning 73
memory
base 113
messages
alert 97
critical error 96
warning 97
misformed characters 93
modem speed 114
MSDS (Material Safety Data Sheets) 128
multiple pages, printing on single sheet 39

N

n-up printing 39

O

OCR (optical character recognition)
- software 6
- using 65

operating environment, specifications 111
ordering accessories and parts 132
output bin
- capacity 113
- illustration 4

ozone production 125

P

package contents 2
pages
- blank 78
- crooked 82
- different from what appears on screen 83
- different than on another printer 84
- feeding problems 82
- not printing 79

paper
- common problems 25
- guidelines 25
- optimizing print quality 23
- size, maximum 113
- size, minimum 113
- sizes, default adjustments 14
- specifications 7, 24
- weight 113
- *See also* special media

paper path, cleaning 73
parallel cable, ordering 132
parallel port 4, 114
part numbers 132
parts and accessories 132
path of media, cleaning 73
PCL 5e printer driver 20
PCL 6 printer driver 20
photo scanning
- troubleshooting 106

physical specifications
- device 111

picture scanning
- troubleshooting 106

port availability 114
ports
- cannot access 81
- on device 4
- on printer 114

PostScript printer driver 20
power cord
- ordering 132

power problems 76
power receptacle 4
power specifications
- device 111

power switch 4
PowerSave mode 111
preprinted forms, printing 35
print cartridge
- HP policy on non-HP print cartridges 134
- installing 134
- life expectancy 134
- ordering 132
- recycling 134
- saving toner 135
- storing 134

print jobs, canceling 19
print quality
- changing 21
- improving 89
- optimizing for media types 23
- understanding settings 21

printer
- capacities and ratings 113
- drivers, requirements for 20
- media path cleaning 73

printing
- booklets 40
- both sides of media 37
- canceling 19
- card stock 36
- custom media 36
- device control panel menu map 13
- envelopes 30
- letterhead 35
- multiple pages on a single sheet 39
- preprinted forms 35
- speed 113
- transparencies and labels 33
- troubleshooting 76, 98
- using manual feed 18
- watermarks 42

printing supplies
- ordering 132

product numbers 132
programming
- Scan to button 60

ProRes 1200 print-quality setting 21
PS printer driver 20

R

Readiris OCR 6
recycling
- print cartridges 134
- program 126

reduced size 105
reducing
- copies 49

repackaging guidelines 138
repeating defects, troubleshooting 92

replacement parts, ordering 133
resolution
faxing 114
printing 113
scanning 66, 114
restoring factory settings 13
returning the unit 138
returns for supplies 126
ring volume
adjusting 15

S
safety
statements 121
saving print cartridge toner 135
scan quality
improving and preventing problems 110
troubleshooting 106
scanner capacities and ratings 113
scanning
canceling 59
color 66
error messages 109
LaserJet Scan software 61
margins 114
methods 58
OCR, using 65
quality, improving 110
resolution 66, 114
takes too long 108
to a file 61
to a folder 60
to e-mail 60
troubleshooting 106
TWAIN, using 64
WIA, using 64
separation pad, ordering 133
service
hardware 138
information form 141
settings
changing defaults 9
changing from the computer 20
restoring factory default 13
shipping damage 138
size
device 111
media 7
size reduced 105
skewed pages 93
skewed printing 82
smeared toner 91
software components 6
special media
specifications 28
specifications
ADF 29, 114
battery 115
card stock and heavy media 27
copier capacities and ratings 113
envelopes 26
labels 25
media 7, 24
printer capacities and ratings 113
scanner capacities and ratings 113
transparencies 26
specs on media 89
speed
copy 113
fax 114
modem 114
print 113
standby power specifications 111
statements
Australian EMC 123
Declaration of Conformity 121, 124
extended warranty 140
FCC Part 68 requirements 118
FCC regulations 118
Finland laser 122
IC CS-03 requirements 120
Korean EMI 122
laser safety 121
telephone consumer protection act 119
warranty 129
storage environment, specifications 111
storing print cartridges 134
streaks 105
supplies
ordering 132
support, customer. *See* customer support
SupportPack 140

T
telephone consumer protection act 119
telephone lines
fax tone volume, adjusting 15
telephone port 4
temperature
specifications 111
terminology 143
text
garbled, incorrect, or incomplete 83
missing 83, 107
toner
consumption 125
loose 92
saving 21, 135
scattered outline 95
smear 91
specks 89
transparencies
media sizes and weights 7
printing 33

specifications for 26
troubleshooting
black dots 110
blank pages 78, 100, 110
characters, misformed 93
copy output 99
copying 99
creases 94
curled media 82
curling paper 94
dropouts 90
error messages 81
faded print 89
feeding problems 79, 82
graphics 83, 84, 106
gray backgrounds 91
light print 89
lines 90, 110
list of problems 75
loose toner 92
media guides 82
media jams 85
media problems 25
not responding 76, 79, 81
pages not printing 79
paper 107
parallel ports 81
pickup roller 82
power on 76
printer 76, 98
quality, image 106
repeating defects 92
scanning 106
sizes, wrong 107
skewed pages 93, 106
skewed print 82
smears 91
specks 89, 95
streaks 110
text problems 83, 107, 110
too dark 110
too light 110
vertical repetitive defects 92
wrinkles 94
See also image quality, troubleshooting
turn on, device does not 76
TWAIN
error message 109
scanning with 64
two-sided originals
copying 54
two-sided printing 37

U
unclear text 105
uninstaller 6
USB
cable, ordering 132
port 4, 114

V
vertical lines 90
vertical repetitive defects 92
vertical white or faded stripes 104
volume
adjusting 14
device control panel key-press, adjusting 16
volume, adjusting 14

W
warning messages 97
warranty
extended 140
limited one-year 129
watermarks, printing 42
weight
ADF media 114
device 111
media 7, 113
white or faded stripes 104
WIA
scanning with 64
width, device 111
wrinkling, troubleshooting 94

© 2003 Hewlett-Packard Development Company, LP

www.hp.com/support/lj3015

Q2669-90902